

Package ‘bibliorefer’

May 7, 2026

Type Package

Title Generator of Main Scientific References

Version 0.1.3

Maintainer Márcio Eustáquio <marcioeustaquio@id.uff.br>

Description Generates a list, with a size defined by the user, containing the main scientific references and the frequency distribution of authors and journals in the list obtained. The database is a dataframe with academic production metadata made available by bibliographic collections such as Scopus, Web of Science, etc. The temporal evolution of scientific production on a given topic is presented and ordered lists of articles are constructed by number of citations and of authors and journals by level of productivity. Massimo Aria, Corrado Cuccurullo. (2017) <[doi:10.1016/j.joi.2017.08.007](https://doi.org/10.1016/j.joi.2017.08.007)>. Caibo Zhou, Wenyan Song. (2021) <[doi:10.1016/j.jclepro.2021.126943](https://doi.org/10.1016/j.jclepro.2021.126943)>.

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.2

Imports stats

Depends R (>= 4.4.0)

NeedsCompilation no

Author Márcio Eustáquio [aut, cre]

Repository CRAN

Date/Publication 2026-02-07 06:11:07 UTC

Contents

ajust_pagin	2
arquivos_une	3
auxinf_autr	4
convert_biblioscopus	5
convert_bibliowos	6
crit_quant	7
entrada_scopus	8

entrada_wos	9
example_database	10
junt_scopuswos	10
principal_lister	12
produc_cientific	13
tabel_gera	14

Index	15
--------------	-----------

ajust_pagin	<i>Function of standardizing spacing between Scopus and Web of Science pages</i>
-------------	--

Description

This function adjusts the spacing between article pages to the standard bibtex format.

Usage

```
ajust_pagin(input_ent)
```

Arguments

input_ent	input_ent is a dataframe with the list of main scientifics references generated by the principal_listr function
-----------	---

Value

This function returns a dataframe object containing the main list of articles, with the spacing between article pages adjusted to the standard bibtex format.

References

- 1 - Asymptotic Theory of Statistics and Probability. Anirban DasGupta. New York: Springer Science+Business Media, LLC, 2008.
- 2 - Quantitative science studies should be framed with middle-range theories and concepts from the social sciences Heinze, T., Jappe, A. Quantitative Science Studies, 1(3), pp. 983–992, 2020

Examples

```
#Call the principal_lister function
input_tam <- 100
file_db <- system.file("extdata", "example_database.csv", package = "bibliorefer")
separator <- ";"
input_date <- example_database(file_db, separator)
principal_refer <- principal_lister(input_date, input_tam)

#Call the ajust_pagin function
ajust_space <- ajust_pagin(principal_refer)
```

ajust_space

arquiwos_une	<i>Function that consolidates files in BibTeX format from the WoS database.</i>
--------------	---

Description

The function combines the various Bibtex files from the WoS collection into a single file. The function returns a list with the sequence of grouped files and a dataframe with the final Bibtex database.

Usage

```
arquiwos_une(arquivos)
```

Arguments

`arquivos` is the database that contains the metadata in Bibtex format for the articles in the WoS collection.

Value

This function returns a dataframe containing the metadata for the articles in the WoS collection.

References

Aria, M. & Cuccurullo, C. (2017) bibliometrix: An R-tool for comprehensive science mapping analysis, *Journal of Informetrics*, 11(4), pp 959-975, Elsevier

Examples

```
#Call the arquiwos_une function

file_db <- system.file("extdata", "savedreccs.bib", package = "bibliorefer")
cabec_wos = TRUE
quoaspa_wos = ""
arquivos <- entrada_wos(file_db, cabec_wos, quoaspa_wos)

#Call the arquiwos_une function
base_arquiwos <- arquiwos_une(arquivos)
base_arquiwos
```

`auxinf_autr`*Function with information about scientific partnerships*

Description

This function generates quantitative information about the partnerships of researchers in the development of scientific production on the topic covered. The function returns a list containing 5 dataframes with information about the number of authors who wrote the articles and the number of articles written by each author, both in the general database and in the list of main references.

Usage

```
auxinf_autr(input_date, input_tam)
```

Arguments

<code>input_date</code>	is a dataframe with the scientific production database
<code>input_tam</code>	is the length of the dataframe to be generated with the main articles, authors and journals

Value

The function returns a list containing 5 dataframes with information about the number of authors who wrote the articles and the number of articles written by each author, both in the general database and in the list of main references.

References

Digitalization as a way forward: A bibliometric analysis of 20 Years of servitization research Zhou, C., Song, W. Journal of Cleaner Production, 300, 2021.

Examples

```
file_db <- system.file("extdata", "example_database.csv", package = "bibliorefer")
separator <- ";"
input_date <- example_database(file_db, separator)
input_tam <- 100
extra_inf <- auxinf_autr(input_date, input_tam)
extra_inf
```

convert_biblioscopus *Function that converts the BibTeX format from the Scopus database to a CSV spreadsheet.*

Description

The function converts the Scopus database metadata file from Bibtex format to a CSV spreadsheet. The function's input is a file with the .bib extension. The function returns a dataframe.

Usage

```
convert_biblioscopus(variavel1, variavel2)
```

Arguments

variavel1 is the database that contains the input and output keys for metadata in Bibtex format for articles in the Scopus collection.

variavel2 is the database that contains the metadata in Bibtex format for articles in the Scopus collection.

Value

This function returns a dataframe containing the metadata for the articles in the Scopus collection.

References

Aria, M. & Cuccurullo, C. (2017) bibliometrix: An R-tool for comprehensive science mapping analysis, Journal of Informetrics, 11(4), pp 959-975, Elsevier

Examples

```
#Call the convert_biblioscopus function

file_db <- system.file("extdata", "scopus.bib", package = "bibliorefer")
cabec = TRUE
quoaspa = ""
base_scopus <- entrada_scopus(file_db, cabec, quoaspa)
base_scopus <- as.data.frame(base_scopus)
variavel1 <- base_scopus$V1
variavel2 <- base_scopus$V2

#Call the convert_biblioscopus function
font_scopus <- convert_biblioscopus(variavel1,variavel2)
font_scopus
```

convert_bibliowos	<i>Function that converts the BibTeX format from the WoS database to a CSV spreadsheet.</i>
-------------------	---

Description

The function converts the WoS database metadata file from Bibtex format to a CSV spreadsheet. The function's input is a file with the .bib extension. The function returns a dataframe.

Usage

```
convert_bibliowos(arquivos)
```

Arguments

arquivos is the database that contains the metadata in Bibtex format for the articles in the WoS collection.

Value

This function returns a dataframe containing the metadata for the articles in the WoS collection.

References

Aria, M. & Cuccurullo, C. (2017) bibliometrix: An R-tool for comprehensive science mapping analysis, Journal of Informetrics, 11(4), pp 959-975, Elsevier

Examples

```
#Call the convert_bibliowos function

file_db <- system.file("extdata","savedrecs.bib", package = "bibliorefer")
cabec_wos = TRUE
quoaspa_wos = ""
arquivos <- entrada_wos(file_db, cabec_wos, quoaspa_wos)

#Call the convert_bibliowos function
font_wos <- convert_bibliowos(arquivos)
font_wos
```

`crit_quant`*Function of quantitative validation criteria*

Description

This function quantitatively validates the list of main scientific references obtained. The function input is a list object with the two dataframes generated by the `principal_lister` function. The `crit_quant` function returns a list of two dataframes with the quantitative criteria that validate the list of main scientific references obtained.

Usage

```
crit_quant(input_ent)
```

Arguments

`input_ent` `input_ent` is a dataframe with the list of main scientific references generated by the `principal_lister` function

Value

The function return a list object with two dataframes with quantitative criteria that validate the list of main scientific references

References

- 1 - Asymptotic Theory of Statistics and Probability. Anirban DasGupta. New York: Springer Science+Business Media, LLC, 2008.
- 2 - Quantitative science studies should be framed with middle-range theories and concepts from the social sciences Heinze, T., Jappe, A. Quantitative Science Studies, 1(3), pp. 983–992, 2020

Examples

```
#Call the principal_lister function
input_tam <- 100
file_db <- system.file("extdata", "example_database.csv", package = "bibliorefer")
separator <- ";"
input_date <- example_database(file_db, separator)
principal_refer <- principal_lister(input_date, input_tam)

#Call the crit_quant function
quant_validation <- crit_quant(principal_refer)
quant_validation[[1]]
quant_validation[[2]]
```

entrada_scopus	<i>Function that generates the test database</i>
----------------	--

Description

The `example_database` function reads a csv file available on the computer system and returns a dataframe as an example of a database to be used by the functions of the `bibliorefer` package

Usage

```
entrada_scopus(path_date, cabec, quoaspa)
```

Arguments

<code>path_date</code>	is a directory path containing the csv file
<code>cabec</code>	is the header for files in bib format
<code>quoaspa</code>	is the separator for files in bib format

Value

This function return is a dataframe with database

References

Aria, M. & Cuccurullo, C. (2017) `bibliometrix`: An R-tool for comprehensive science mapping analysis, *Journal of Informetrics*, 11(4), pp 959-975, Elsevier

Examples

```
#Call the example_database function

file_db <- system.file("extdata", "scopus.bib", package = "bibliorefer")
cabec = TRUE
quoaspa = ""
date_sreference <- entrada_scopus(file_db, cabec, quoaspa)
date_sreference
```

entrada_wos	<i>Function that generates the test database</i>
-------------	--

Description

The `example_database` function reads a csv file available on the computer system and returns a dataframe as an example of a database to be used by the functions of the `bibliorefer` package

Usage

```
entrada_wos(path_date, cabec_wos, quoaspa_wos)
```

Arguments

<code>path_date</code>	is a directory path containing the bib file
<code>cabec_wos</code>	is the header for wos files in bib format
<code>quoaspa_wos</code>	is the separator wos for files in bib format

Value

This function return is a dataframe with database

References

Aria, M. & Cuccurullo, C. (2017) `bibliometrix`: An R-tool for comprehensive science mapping analysis, *Journal of Informetrics*, 11(4), pp 959-975, Elsevier

Examples

```
#Call the example_database function

file_db <- system.file("extdata","savedreccs.bib", package = "bibliorefer")
cabec_wos = TRUE
quoaspa_wos = ""
date_wosrefer <- entrada_wos(file_db, cabec_wos, quoaspa_wos)
date_wosrefer
```

example_database	<i>Function that generates the test database</i>
------------------	--

Description

The `example_database` function reads a csv file available on the computer system and returns a dataframe as an example of a database to be used by the functions of the `bibliorefer` package

Usage

```
example_database(path_date, separator)
```

Arguments

<code>path_date</code>	is a directory path containing the csv file
<code>separator</code>	is the separator for files in csv format

Value

This function return is a dataframe with database

References

Aria, M. & Cuccurullo, C. (2017) `bibliometrix`: An R-tool for comprehensive science mapping analysis, *Journal of Informetrics*, 11(4), pp 959-975, Elsevier

Examples

```
#Call the example_database function

file_db <- system.file("extdata","example_database.csv", package = "bibliorefer")
separator <- ";"
date_sreference <- example_database(file_db, separator)
date_sreference
```

junt_scopuswos	<i>This function converts the BibTeX format from the Scopus and WoS databases to a CSV spreadsheet.</i>
----------------	---

Description

This function converts metadata files from the Scopus and WoS databases in BibTeX format to a CSV spreadsheet. The function takes `.bib` files from the Scopus and WoS collections as input and returns a dataframe.

Usage

```
junt_scopuswos(font_scopus, font_wos)
```

Arguments

font_scopus is the database that contains the metadata in Bibtex format for articles in the Scopus collection.

font_wos is the database that contains the metadata in Bibtex format for articles in the WoS collection.

Value

This function returns a dataframe containing the metadata for the articles in the Scopus and WoS collections.

References

Aria, M. & Cuccurullo, C. (2017) bibliometrix: An R-tool for comprehensive science mapping analysis, *Journal of Informetrics*, 11(4), pp 959-975, Elsevier

Examples

```
#Call the junt_scopuswos function

file_db <- system.file("extdata","scopus.bib", package = "bibliorefer")
cabec = TRUE
quoaspa = ""
base_scopus <- entrada_scopus(file_db, cabec, quoaspa)
base_scopus <- as.data.frame(base_scopus)
variavel1 <- base_scopus$V1
variavel2 <- base_scopus$V2

#Call the convert_biblioscopus function
font_scopus <- convert_biblioscopus(variavel1,variavel2)

#Call the convert_bibliowos function

file_db <- system.file("extdata","savedrecs.bib", package = "bibliorefer")
cabec_wos = TRUE
quoaspa_wos = ""
arquivos <- entrada_wos(file_db, cabec_wos, quoaspa_wos)

#Call the convert_bibliowos function
font_wos <- convert_bibliowos(arquivos)

#Call the junt_scopuswos function
font_scopuswos <- junt_scopuswos(font_scopus,font_wos)
font_scopuswos
```

principal_lister *Function of principal scientifics references*

Description

This function generates a list, with a size defined by the user, with the main scientific references and also generates quantitative parameters about authors and journals.

Usage

```
principal_lister(input_date, input_tam)
```

Arguments

`input_date` is a dataframe with the scientific production database
`input_tam` is the length of the dataframe to be generated with the main articles, authors and journals

Value

This function returns a list object with two dataframes. The first dataframe, with a length defined by the user, containing the list of articles ordered by the number of citations crossed with the lists of authors and journals ordered by the number of articles published. The second dataframe contains quantitative parameters about authors and journals that are necessary to create the quantitative validation criterion for the list obtained.

References

A bibliometric analysis of Journal of Higher Education Management (JHEM) from 2007 to 2016. Antia-Obong, S.E., Casselden, B., Pickard, A. Library Philosophy and Practice, 2019.

Examples

```
#Call the principal_lister function

# Example 1
input_tam <- 80
file_db <- system.file("extdata", "example_database.csv", package = "bibliorefer")
separator <- ";"
input_date <- example_database(file_db, separator)
principal_refer <- principal_lister(input_date, input_tam)
principal_refer[[1]]

# Example 2
input_tam <- 40
file_db <- system.file("extdata", "example_database.csv", package = "bibliorefer")
separator <- ";"
input_date <- example_database(file_db, separator)
principal_refer <- principal_lister(input_date, input_tam)
```

```
principal_refer[[1]]
```

produc_cientific	<i>Function of annual scientific production</i>
------------------	---

Description

This function shows the evolution of scientific production. The function receives a dataframe with scientific production data and returns a dataframe with the dates and number of articles published on each date

Usage

```
produc_cientific(input_date)
```

Arguments

`input_date` is a dataframe with the scientific production database

Value

The function return a dataframe with the dates and the number of articles published in each of them

References

Evolution of number of citations per article in Materials Science: possible causes and effect on the impact factor of journals. Ariza-Guerrero, A.M, Blázquez, J.S. *Scientometrics*, 128(12), pp. 6589–6609. 2023.

Examples

```
#Call the produc_cientific function
file_db <- system.file("extdata","example_database.csv", package = "bibliorefer")
separator <- ";"
input_date <- example_database(file_db, separator)
prod_ct <- produc_cientific(input_date)
prod_ct
```

tabel_gera	<i>Function of scientific information</i>
------------	---

Description

This function receives a dataframe with scientific production data and returns a list object with information about articles, authors and journals.

Usage

```
tabel_gera(input_date)
```

Arguments

`input_date` is a dataframe with the scientific production database

Value

The function return a list object containing three dataframes with ordered lists of articles, authors and journals.

References

Aria, M. & Cuccurullo, C. (2017) bibliometrix: An R-tool for comprehensive science mapping analysis, *Journal of Informetrics*, 11(4), pp 959-975, Elsevier

Examples

```
#Call the tabel_gera function
file_db <- system.file("extdata", "example_database.csv", package = "bibliorefer")
separator <- ";"
input_date <- example_database(file_db, separator)
scientific_inf <- tabel_gera(input_date)
scientific_inf
```

Index

ajust_pagin, [2](#)
arquiwos_une, [3](#)
auxinf_autr, [4](#)

convert_biblioscopus, [5](#)
convert_bibliowos, [6](#)
crit_quant, [7](#)

entrada_scopus, [8](#)
entrada_wos, [9](#)
example_database, [10](#)

junt_scopuswos, [10](#)

principal_lister, [12](#)
produc_cientific, [13](#)

tabel_gera, [14](#)