

Package ‘greta.gp’

July 21, 2026

Type Package

Title Gaussian Process Modelling in 'greta'

Version 0.2.3

Description Provides a syntax to create and combine Gaussian process kernels in 'greta'. You can then use these kernels to define either full rank or sparse Gaussian processes, and project a fitted process to new coordinates. This lets you include Gaussian process components in the statistical models you write with 'greta'. This is an extension to the 'greta' software, Golding (2019) <doi:10.21105/joss.01601>.

License Apache License (>= 2)

URL <https://github.com/greta-dev/greta.gp>,
<https://greta-dev.github.io/greta.gp/>

BugReports <https://github.com/greta-dev/greta.gp/issues>

Depends greta (>= 0.6.0), R (>= 4.1.0)

Imports cli, glue, rlang (>= 1.1.4), tensorflow (>= 2.7.0)

Suggests covr, knitr, rmarkdown, spelling, testthat (>= 3.1.0)

VignetteBuilder knitr

Config/testthat/edition 3

Config/Needs/website greta-dev/greta.pkgdown

Encoding UTF-8

Language en-GB

SystemRequirements Python (>= 3.7.0) with header files and shared library; TensorFlow (>= v2.0.0; <https://www.tensorflow.org/>); TensorFlow Probability (v0.8.0; <https://www.tensorflow.org/probability/>)

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Nick Golding [aut, cph] (ORCID:
<https://orcid.org/0000-0001-8916-5570>),
Jian Yen [ctb],
Nicholas Tierney [aut, cre] (ORCID:
<https://orcid.org/0000-0003-1460-8722>)
Maintainer Nicholas Tierney <nicholas.tierney@gmail.com>
Repository CRAN
Date/Publication 2026-07-21 08:20:17 UTC

Contents

gp	2
greta.gp	3
kernels	4
Index	7

gp	<i>Define a Gaussian process</i>
----	----------------------------------

Description

Define Gaussian processes, and project them to new coordinates.

Usage

```
gp(x, kernel, inducing = NULL, n = 1, tol = 1e-04)

project(f, x_new, kernel = NULL)
```

Arguments

x, x_new	greta array giving the coordinates at which to evaluate the Gaussian process
kernel	a kernel function created using one of the kernel() methods
inducing	an optional greta array giving the coordinates of inducing points in a sparse (reduced rank) Gaussian process model
n	the number of independent Gaussian processes to define with the same kernel
tol	a numerical tolerance parameter, added to the diagonal of the self-covariance matrix when computing the cholesky decomposition. If the sampler is hitting a lot of numerical errors, increasing this parameter could help
f	a greta array created with gp\$gp representing the values of one or more Gaussian processes

Details

`gp()` returns a greta array representing the values of the Gaussian process (or processes) evaluated at x . This Gaussian process can be made sparse (via a reduced-rank representation of the covariance) by providing an additional set of inducing point coordinates `inducing`. `project()` evaluates the values of an existing Gaussian process (created with `gp()`) to new data.

Value

A greta array

Examples

```
## Not run:
# build a kernel function on two dimensions
k1 <- rbf(lengthscales = c(0.1, 0.2), variance = 0.6)
k2 <- bias(variance = lognormal(0, 1))
K <- k1 + k2

# use this kernel in a full-rank Gaussian process
f <- gp(1:10, K)

# or in sparse Gaussian process
f_sparse <- gp(1:10, K, inducing = c(2, 5, 8))

# project the values of the GP to new coordinates
f_new <- project(f, 11:15)

# or project with a different kernel (e.g. a sub-kernel)
f_new_bias <- project(f, 11:15, k2)

## End(Not run)
```

greta.gp

Gaussian process modelling in greta

Description

A greta module to create and combine covariance functions and use them to build Gaussian process models in greta. See [kernels\(\)](#) and [gp\(\)](#)

Author(s)

Maintainer: Nicholas Tierney <nicholas.tierney@gmail.com> ([ORCID](#))

Authors:

- Nicholas Tierney <nicholas.tierney@gmail.com> ([ORCID](#))
- Nick Golding <nick.golding.research@gmail.com> ([ORCID](#)) [copyright holder]

Other contributors:

- Jian Yen [contributor]

See Also

Useful links:

- <https://github.com/greta-dev/greta.gp>
- <https://greta-dev.github.io/greta.gp/>
- Report bugs at <https://github.com/greta-dev/greta.gp/issues>

kernels

Gaussian process kernels

Description

Create and combine Gaussian process kernels (covariance functions) for use in Gaussian process models.

Usage

```
bias(variance)

constant(variance)

white(variance)

iid(variance, columns = 1)

rbf(lengthscales, variance, columns = seq_along(lengthscales))

rational_quadratic(
  lengthscales,
  variance,
  alpha,
  columns = seq_along(lengthscales)
)

linear(variances, columns = seq_along(variances))

polynomial(variances, offset, degree, columns = seq_along(variances))

expo(lengthscales, variance, columns = seq_along(lengthscales))

mat12(lengthscales, variance, columns = seq_along(lengthscales))

mat32(lengthscales, variance, columns = seq_along(lengthscales))

mat52(lengthscales, variance, columns = seq_along(lengthscales))
```

```
cosine(lengthscales, variance, columns = seq_along(lengthscales))
```

```
periodic(period, lengthscale, variance)
```

Arguments

variance, variances	(scalar/vector) the variance of a Gaussian process prior in all dimensions (variance) or in each dimension (variances)
columns	(scalar/vector integer, not a greta array) the columns of the data matrix on which this kernel acts. Must have the same dimensions as lengthscale parameters.
alpha	(scalar) additional parameter in rational quadratic kernel
offset	(scalar) offset in polynomial kernel
degree	(scalar) degree of polynomial kernel
period	(scalar) the period of the Gaussian process
lengthscale, lengthscales	(scalar/vector) the correlation decay distance along all dimensions (lengthscale) or each dimension ((lengthscales)) of the Gaussian process

Details

The kernel constructor functions each return a *function* (of class `greta_kernel`) which can be executed on greta arrays to compute the covariance matrix between points in the space of the Gaussian process. The `+` and `*` operators can be used to combine kernel functions to create new kernel functions.

Note that `bias` and `constant` are identical names for the same underlying kernel.

`iid` is equivalent to `bias` where all entries in `columns` match (where the absolute euclidean distance is less than $1e-12$), and `white` where they don't; i.e. an independent Gaussian random effect.

Value

greta kernel with class "greta_kernel"

Examples

```
## Not run:
# create a radial basis function kernel on two dimensions
k1 <- rbf(lengthscales = c(0.1, 0.2), variance = 0.6)

# evaluate it on a greta array to get the variance-covariance matrix
x <- greta_array(rnorm(8), dim = c(4, 2))
k1(x)

# non-symmetric covariance between two sets of points
x2 <- greta_array(rnorm(10), dim = c(5, 2))
k1(x, x2)

# create a bias kernel, with the variance as a variable
```

```
k2 <- bias(variance = lognormal(0, 1))

# combine two kernels and evaluate
K <- k1 + k2
K(x, x2)

# other kernels
constant(variance = lognormal(0, 1))
white(variance = lognormal(0, 1))
iid(variance = lognormal(0, 1))
rational_quadratic(lengthscales = c(0.1, 0.2), alpha = 0.5, variance = 0.6)
linear(variances = 0.1)
polynomial(variances = 0.6, offset = 0.8, degree = 2)
expo(lengthscales = 0.6, variance = 0.9)
mat12(lengthscales = 0.5, variance = 0.7)
mat32(lengthscales = 0.4, variance = 0.8)
mat52(lengthscales = 0.3, variance = 0.9)
cosine(lengthscales = 0.68, variance = 0.8)
periodic(period = 0.71, lengthscale = 0.59, variance = 0.2)

## End(Not run)
```

Index

`bias (kernels)`, [4](#)

`constant (kernels)`, [4](#)

`cosine (kernels)`, [4](#)

`expo (kernels)`, [4](#)

`gp`, [2](#)

`gp()`, [3](#)

`greta.gp`, [3](#)

`greta.gp-package (greta.gp)`, [3](#)

`iid (kernels)`, [4](#)

`kernel()`, [2](#)

`kernels`, [4](#)

`kernels()`, [3](#)

`linear (kernels)`, [4](#)

`mat12 (kernels)`, [4](#)

`mat32 (kernels)`, [4](#)

`mat52 (kernels)`, [4](#)

`periodic (kernels)`, [4](#)

`polynomial (kernels)`, [4](#)

`project (gp)`, [2](#)

`rational_quadratic (kernels)`, [4](#)

`rbf (kernels)`, [4](#)

`white (kernels)`, [4](#)