

Package ‘neuromapr’

May 9, 2026

Title Spatial Null Models and Transforms for Brain Map Comparison

Version 0.2.2

Description Implements spatial null models and coordinate-space transformations for statistical comparison of brain maps, following the framework described in Markello et al. (2022) [doi:10.1038/s41592-022-01625-w](https://doi.org/10.1038/s41592-022-01625-w). Provides variogram-matching surrogates (Burt et al. 2020), Moran spectral randomization (Wagner & Dray 2015), and spin-based permutation tests (Alexander-Bloch et al. 2018). Includes an R interface to the 'neuromaps' annotation registry for browsing, downloading, and comparing brain map annotations from the Open Science Framework ('OSF'). Integrates with 'ciftiTools' for coordinate-space transforms.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Config/testthat/edition 3

Config/testthat/parallel true

Depends R (>= 4.2.0)

Imports cli, dplyr, ggplot2, gifti, httr2, igraph, lifecycle, rlang, stats, tibble, tools, withr

Suggests ciftiTools, clue, freesurferformats, jsonlite, knitr, rmarkdown, RNifti, RSpectra, testthat (>= 3.0.0), vcr (>= 1.0.0)

VignetteBuilder knitr

URL <https://github.com/lcbc-uio/neuromapr>,
<https://lcbc-uio.github.io/neuromapr/>,
<https://doi.org/10.5281/zenodo.18648937>

BugReports <https://github.com/lcbc-uio/neuromapr/issues>

NeedsCompilation no

Author Athanasia Mo Mowinckel [aut, cre, cph] (ORCID:
<https://orcid.org/0000-0002-5756-0223>)

Maintainer Athanasia Mo Mowinckel <a.m.mowinckel@psykologi.uio.no>

Repository CRAN

Date/Publication 2026-04-30 07:50:03 UTC

Contents

annot_to_gifti	2
check_wb_command	3
clear_neuromaps_cache	4
compare_maps	4
fetch_neuromaps_annotation	5
fsmorph_to_gifti	6
generate_nulls	7
get_parcel_centroids	8
get_surface_distance	9
make_surf_graph	10
neuromaps_available	11
null_alexander_bloch	12
null_baum	13
null_burt2018	14
null_burt2020	14
null_cornblath	16
null_distribution	17
null_moran	18
null_spin_vasa	19
parcellate	20
parcels_to_vertices	21
permtest_metric	21
read_brain_map_values	23
resample_images	23
transform_to_space	25
unparcellate	26
vertex_areas	27
vertices_to_parcels	27

Index **29**

annot_to_gifti	<i>Convert FreeSurfer annotation to GIFTI</i>
----------------	---

Description

Reads a FreeSurfer .annot file and writes a GIFTI label file.

Usage

```
annot_to_gifti(annot_path, output_path = NULL)
```

Arguments

annot_path Path to FreeSurfer .annot file.
output_path Output GIFTI path. If NULL, replaces the extension with .label.gii.

Value

The output file path (invisibly).

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
## Not run:  
annot_to_gifti("lh.aparc.annot")  
annot_to_gifti("lh.aparc.annot", "lh.aparc.label.gii")  
  
## End(Not run)
```

check_wb_command *Check for Connectome Workbench*

Description

Verifies that wb_command is available. If wb_path is NULL, checks ciftiTools default and system PATH.

Usage

```
check_wb_command(wb_path = NULL)
```

Arguments

wb_path Optional explicit path to wb_command.

Value

Path to wb_command executable.

Examples

```
## Not run:  
check_wb_command()  
  
## End(Not run)
```

`clear_neuromaps_cache` *Clear cached neuromaps registry data*

Description

Removes the session-level cache of the neuromaps annotation registry, forcing a fresh download on the next call to `neuromaps_available()` or `fetch_neuromaps_annotation()`.

Usage

```
clear_neuromaps_cache()
```

Value

NULL, invisibly.

Examples

```
clear_neuromaps_cache()
```

`compare_maps` *Compare brain maps with spatial null model significance testing*

Description

Computes the correlation between two brain maps and optionally tests significance using a spatial null model to account for spatial autocorrelation.

Usage

```
compare_maps(
  x,
  y,
  method = c("pearson", "spearman"),
  null_method = NULL,
  n_perm = 1000L,
  nulls = NULL,
  distmat = NULL,
  coords = NULL,
  seed = NULL,
  na.rm = TRUE,
  verbose = TRUE,
  ...
)

## S3 method for class 'neuromaps_enhanced_comparison'
print(x, ...)
```

Arguments

x, y	Numeric vectors of brain map values, or file paths to GIFTI/NIfTI files.
method	Correlation method: "pearson" or "spearman".
null_method	Optional null model method for empirical p-values. One of "burt2020", "moran", "spin_vasa", "spin_hungarian", "alexander_bloch", "baum", "cornblath", "burt2018", or NULL for parametric only.
n_perm	Integer number of null permutations.
nulls	Pre-computed null_distribution object for x.
distmat	Distance matrix (passed to null model if needed).
coords	Coordinate list (passed to spin null models if needed).
seed	Optional integer seed for reproducibility.
na.rm	Logical, remove NA values before computing correlation.
verbose	Logical, print progress messages.
...	Additional arguments passed to generate_nulls() .

Value

A `neuromaps_enhanced_comparison` object (inherits `neuromaps_comparison`) with additional fields `p_null`, `null_method`, `null_r`, and `n_perm`.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
x <- rnorm(50)
y <- x + rnorm(50)
compare_maps(x, y, verbose = FALSE)
```

fetch_neuromaps_annotation

Download a neuromaps annotation

Description

Download brain map annotation files from the neuromaps OSF repository. Surface annotations return two files (left and right hemispheres), volume annotations return one.

Usage

```

fetch_neuromaps_annotation(
  source,
  desc,
  space,
  density = NULL,
  resolution = NULL,
  hemisphere = NULL,
  data_dir = neuromaps_cache_dir(),
  overwrite = FALSE,
  verbose = TRUE
)

```

Arguments

source	Data source identifier (e.g. "abagen", "beliveau").
desc	Map descriptor key (e.g. "genepc1", "feobv").
space	Coordinate space (e.g. "fsaverage", "MNI152", "fsLR").
density	Surface vertex density (e.g. "10k", "164k"). Mutually exclusive with resolution.
resolution	Volume voxel resolution (e.g. "1mm", "2mm"). Mutually exclusive with density.
hemisphere	Hemisphere ("L" or "R").
data_dir	Directory for cached downloads. Defaults to neuromaps_cache_dir().
overwrite	Re-download even if cached file exists.
verbose	Print progress messages.

Value

Character vector of downloaded file path(s).

Examples

```

fetch_neuromaps_annotation("abagen", "genepc1", "fsaverage", density = "10k")

```

fsmorph_to_gifti

Convert FreeSurfer morphometry to GIFTI

Description

Reads a FreeSurfer morphometry file (.curv, .thickness, .sulc) and writes a GIFTI func file.

Usage

```

fsmorph_to_gifti(morph_path, output_path = NULL)

```

Arguments

morph_path Path to FreeSurfer morphometry file.
output_path Output GIFTI path. If NULL, replaces the extension with .func.gii.

Value

The output file path (invisibly).

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
## Not run:  
fsmorph_to_gifti("lh.thickness")  
fsmorph_to_gifti("lh.thickness", "lh.thickness.func.gii")  
  
## End(Not run)
```

generate_nulls	<i>Generate null distributions for brain map data</i>
----------------	---

Description

Dispatches to the appropriate null model method for generating spatially-constrained surrogate brain maps.

Usage

```
generate_nulls(  
  data,  
  method = c("burt2020", "moran", "spin_vasa", "spin_hungarian", "alexander_bloch",  
             "baum", "cornblath", "burt2018"),  
  n_perm = 1000L,  
  distmat = NULL,  
  coords = NULL,  
  parcellation = NULL,  
  seed = NULL,  
  ...  
)
```

Arguments

data	Numeric vector of brain map values.
method	Character string specifying the null model method.
n_perm	Integer number of null permutations to generate.
distmat	Distance matrix (required for "burt2020", "burt2018", and "moran").
coords	List with \$lh and \$rh coordinate matrices (required for spin methods).
parcellation	Integer vector of parcel labels (required for "baum" and "cornblath").
seed	Optional integer seed for reproducibility.
...	Additional arguments passed to the specific null method (e.g. rotation for spin methods, kernel for moran/burt2020).

Value

A [null_distribution](#) object.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
data <- rnorm(100)
distmat <- as.matrix(dist(seq_len(100)))
nd <- generate_nulls(data, method = "moran", distmat = distmat, n_perm = 10L)
```

get_parcel_centroids *Compute parcel centroids*

Description

Finds the centroid of each parcel using one of three methods.

Usage

```
get_parcel_centroids(
  vertices,
  labels,
  method = c("average", "surface", "geodesic"),
  faces = NULL
)
```

Arguments

vertices	Numeric matrix (n x 3) of vertex coordinates.
labels	Integer vector of parcel labels. 0 and NA are medial wall.
method	Centroid method: "average" (coordinate means), "surface" (vertex closest to the average centroid), or "geodesic" (vertex minimizing sum of geodesic distances within parcel).
faces	Integer matrix (m x 3) of face indices. Required for "geodesic" method.

Value

Numeric matrix (n_parcel x 3) with rownames set to parcel labels.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
vertices <- matrix(rnorm(30), ncol = 3)
labels <- c(1L, 1L, 1L, 2L, 2L, 2L, 3L, 3L, 3L)
get_parcel_centroids(vertices, labels, method = "average")
```

get_surface_distance *Compute geodesic distances on a surface mesh*

Description

Builds a graph from a triangular mesh and computes shortest-path (Dijkstra) distances between vertices.

Usage

```
get_surface_distance(vertices, faces, source_vertices = NULL)
```

Arguments

vertices	Numeric matrix (n x 3) of vertex coordinates.
faces	Integer matrix (m x 3) of face indices (1-indexed).
source_vertices	Optional integer vector of source vertex indices. If NULL, computes the full n x n distance matrix.

Value

Numeric distance matrix. If source_vertices is provided, returns a length(source_vertices) x n matrix; otherwise an n x n matrix.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
vertices <- matrix(  
  c(0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 1),  
  nrow = 4, byrow = TRUE  
)  
faces <- matrix(c(1L, 2L, 3L, 2L, 3L, 4L), nrow = 2, byrow = TRUE)  
get_surface_distance(vertices, faces)
```

make_surf_graph

Build an igraph from a triangular surface mesh

Description

Extracts unique edges from triangular faces, computes Euclidean edge weights, and returns an igraph graph object suitable for geodesic distance computation.

Usage

```
make_surf_graph(vertices, faces)
```

Arguments

vertices Numeric matrix (n x 3) of vertex coordinates.
faces Integer matrix (m x 3) of face indices (1-indexed).

Value

An igraph graph object with weighted edges.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
vertices <- matrix(  
  c(0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 1),  
  nrow = 4, byrow = TRUE  
)  
faces <- matrix(c(1L, 2L, 3L, 2L, 3L, 4L), nrow = 2, byrow = TRUE)  
g <- make_surf_graph(vertices, faces)
```

neuromaps_available *List available neuromaps annotations*

Description

Query the neuromaps registry to see which brain map annotations are available for download. Data is fetched from the [neuromaps](#) project's GitHub repository and cached for the session.

Usage

```
neuromaps_available(
  source = NULL,
  desc = NULL,
  space = NULL,
  density = NULL,
  resolution = NULL,
  hemisphere = NULL,
  tags = NULL,
  format = NULL,
  refresh = FALSE,
  fixed = FALSE
)
```

Arguments

source	Data source identifier (e.g. "abagen", "beliveau").
desc	Map descriptor key (e.g. "genepc1", "feobv").
space	Coordinate space (e.g. "fsaverage", "MNI152", "fsLR").
density	Surface vertex density (e.g. "10k", "164k"). Mutually exclusive with resolution.
resolution	Volume voxel resolution (e.g. "1mm", "2mm"). Mutually exclusive with density.
hemisphere	Hemisphere ("L" or "R").
tags	Character vector of tags. All must match (AND logic).
format	Filter by format ("surface" or "volume").
refresh	Logical. If TRUE, forces a fresh download of the registry data, ignoring any session cache.
fixed	Logical. If TRUE, filter strings are matched literally rather than as regular expressions.

Details

All string filter parameters (source, desc, space, density, resolution, hemisphere, format) are treated as **R regular expressions** and matched with `grepl()`. For example, source = "^beliveau\$" matches exactly, while source = "bel" matches any source containing "bel". Set fixed = TRUE for literal string matching. The tags parameter always uses exact matching (AND logic).

When used in `fetch_neuromaps_annotation()`, source, desc, and space are exact matches.

Value

A tibble of available annotations with columns: source, desc, space, den, res, hemi, format, fname, full_desc, tags, N, age.

Examples

```
neuromaps_available()
neuromaps_available(source = "beliveau")
neuromaps_available(tags = "pet")
```

null_alexander_bloch *Alexander-Bloch spin test null model*

Description

Original vertex-level spin test: rotates coordinates and assigns each rotated vertex the value of its nearest original vertex (no optimal matching).

Usage

```
null_alexander_bloch(
  data,
  coords,
  n_perm = 1000L,
  seed = NULL,
  rotation = c("euler", "rodrigues")
)
```

Arguments

data	Numeric vector of brain map values.
coords	List with \$lh and \$rh matrices of spherical coordinates (n x 3 each).
n_perm	Integer number of null permutations to generate.
seed	Optional integer seed for reproducibility.
rotation	Rotation generation method: "euler" (ZYZ Euler angles, default, matches neuromaps Python) or "rodrigues" (Rodrigues axis-angle formula).

Value

A [null_distribution](#) object.

References

Alexander-Bloch AF et al. (2018) NeuroImage 175:111-120. doi:10.1016/j.neuroimage.2018.04.023

Examples

```
coords <- list(lh = matrix(rnorm(30), 10, 3), rh = matrix(rnorm(30), 10, 3))
data <- rnorm(20)
nd <- null_alexander_bloch(data, coords, n_perm = 10L, seed = 1L)
```

null_baum

Baum spin test null model

Description

Spin-based null model with maximum-overlap parcel reassignment. After rotating vertex coordinates, each original parcel is assigned the value of the rotated parcel with the most vertex overlap.

Usage

```
null_baum(
  data,
  coords,
  parcellation,
  n_perm = 1000L,
  seed = NULL,
  rotation = c("euler", "rodrigues")
)
```

Arguments

data	Numeric vector of brain map values.
coords	List with \$lh and \$rh matrices of spherical coordinates (n x 3 each).
parcellation	Integer vector of parcel labels for all vertices. 0 and NA indicate medial wall.
n_perm	Integer number of null permutations to generate.
seed	Optional integer seed for reproducibility.
rotation	Rotation generation method: "euler" (ZYZ Euler angles, default, matches neuromaps Python) or "rodrigues" (Rodrigues axis-angle formula).

Value

A [null_distribution](#) object.

References

Baum GL et al. (2020) PNAS 117:21854-21861. doi:10.1073/pnas.2005518117

Examples

```
coords <- list(lh = matrix(rnorm(30), 10, 3), rh = matrix(rnorm(30), 10, 3))
parcellation <- c(rep(1L, 5), rep(2L, 5), rep(3L, 5), rep(4L, 5))
data <- c(1.0, 2.0, 3.0, 4.0)
nd <- null_baum(data, coords, parcellation, n_perm = 10L, seed = 1L)
```

null_burt2018	<i>Burt 2018 spatial autoregressive null model</i>
---------------	--

Description

Generates surrogate brain maps using a spatial autoregressive (SAR) model. Estimates spatial auto-correlation and distance decay parameters, then generates surrogates by solving the SAR equation and rank-matching to the original data.

Usage

```
null_burt2018(data, distmat, n_perm = 1000L, seed = NULL)
```

Arguments

data	Numeric vector of brain map values.
distmat	Distance matrix between parcels/vertices.
n_perm	Integer number of null permutations to generate.
seed	Optional integer seed for reproducibility.

Value

A [null_distribution](#) object.

References

Burt JB et al. (2018) Nature Neuroscience 21:1251-1259. doi:10.1038/s41593-018-0195-0

Examples

```
data <- rnorm(50)
distmat <- as.matrix(dist(matrix(rnorm(100), 50, 2)))
nd <- null_burt2018(data, distmat, n_perm = 10L, seed = 1L)
```

null_burt2020	<i>Variogram-matching null model</i>
---------------	--------------------------------------

Description

Generates spatially-constrained surrogate brain maps by matching the empirical variogram of the original data through smoothed random permutations.

Usage

```

null_burt2020(
  data,
  distmat,
  n_perm = 1000L,
  seed = NULL,
  ns = 500L,
  nh = 25L,
  pv = 25,
  knn = 1000L,
  deltas = seq(0.1, 0.9, by = 0.1),
  kernel = c("exponential", "gaussian", "uniform"),
  resample = FALSE
)

```

Arguments

data	Numeric vector of brain map values.
distmat	Distance matrix between parcels/vertices.
n_perm	Integer number of null permutations to generate.
seed	Optional integer seed for reproducibility.
ns	Integer, subsample size for variogram computation.
nh	Integer, number of distance bins for variogram.
pv	Numeric, percentile cutoff for maximum distance in variogram.
knn	Integer, number of nearest neighbors for smoothing.
deltas	Numeric vector of smoothing levels (fractions of knn).
kernel	Smoothing kernel function.
resample	Logical. If FALSE (default, matches brainsmash Python), variogram subsample indices are computed once and reused across all permutations. If TRUE, a fresh subsample is drawn each time.

Value

A [null_distribution](#) object.

References

Burt JB et al. (2020) NeuroImage 220:117038. doi:10.1016/j.neuroimage.2020.117038

Examples

```

data <- rnorm(50)
distmat <- as.matrix(dist(matrix(rnorm(100), 50, 2)))
nd <- null_burt2020(data, distmat, n_perm = 10L, seed = 1L)

```

null_cornblath	<i>Cornblath spin test null model</i>
----------------	---------------------------------------

Description

Spin-based null model where each rotated vertex receives the label of its nearest non-medial-wall original vertex, then parcels are reassigned by majority vote among the resulting vertex labels.

Usage

```

null_cornblath(
  data,
  coords,
  parcellation,
  n_perm = 1000L,
  seed = NULL,
  rotation = c("euler", "rodrigues")
)

```

Arguments

data	Numeric vector of brain map values.
coords	List with \$lh and \$rh matrices of spherical coordinates (n x 3 each).
parcellation	Integer vector of parcel labels for all vertices. 0 and NA indicate medial wall.
n_perm	Integer number of null permutations to generate.
seed	Optional integer seed for reproducibility.
rotation	Rotation generation method: "euler" (ZYZ Euler angles, default, matches neuromaps Python) or "rodrigues" (Rodrigues axis-angle formula).

Value

A [null_distribution](#) object.

References

Cornblath EJ et al. (2020) Communications Biology 3:590. doi:10.1038/s42003-020-01296-5

Examples

```

coords <- list(lh = matrix(rnorm(30), 10, 3), rh = matrix(rnorm(30), 10, 3))
parcellation <- c(rep(1L, 5), rep(2L, 5), rep(3L, 5), rep(4L, 5))
data <- c(1.0, 2.0, 3.0, 4.0)
nd <- null_cornblath(data, coords, parcellation, n_perm = 10L, seed = 1L)

```

null_distribution *Create a null distribution object*

Description

Create a null distribution object

Usage

```
new_null_distribution(nulls, method, observed, params = list())

## S3 method for class 'null_distribution'
print(x, ...)

## S3 method for class 'null_distribution'
summary(object, ...)

## S3 method for class 'null_distribution'
as.matrix(x, ...)

## S3 method for class 'null_distribution'
plot(x, parcel = 1L, ...)
```

Arguments

nulls	Numeric matrix (n x n_perm) of surrogate values.
method	Character string identifying the null model method.
observed	Numeric vector of original data values.
params	Named list of algorithm parameters.
x	A null_distribution object.
...	Ignored.
object	A null_distribution object.
parcel	Integer index of the parcel to plot.

Value

A null_distribution object.

Examples

```
nulls <- matrix(rnorm(30), nrow = 3, ncol = 10)
nd <- new_null_distribution(nulls, "test", observed = c(1, 2, 3))
print(nd)
summary(nd)
```

 null_moran

Moran spectral randomization null model

Description

Generates spatially-constrained surrogate brain maps using Moran's eigenvector maps (MEMs) for spectral randomization.

Usage

```

null_moran(
  data,
  distmat,
  n_perm = 1000L,
  seed = NULL,
  procedure = c("pair", "singleton"),
  kernel = c("inverse_distance", "exponential", "gaussian", "bisquare"),
  tol = 1e-06
)

```

Arguments

data	Numeric vector of brain map values.
distmat	Distance matrix between parcels/vertices.
n_perm	Integer number of null permutations to generate.
seed	Optional integer seed for reproducibility.
procedure	Character, either "pair" (default, random 2D rotations of near-degenerate eigenvector pairs, matches neuromaps Python) or "singleton" (random sign flips of individual eigenvectors).
kernel	Weight matrix kernel: "inverse_distance" (default, matches neuromaps Python), "exponential", "gaussian", or "bisquare".
tol	Numeric tolerance for eigenvalue comparison.

Value

A [null_distribution](#) object.

References

Wagner HH, Dray S (2015) Methods in Ecology and Evolution 6:1169-1178. doi:10.1111/2041-210X.12407

Examples

```

data <- rnorm(50)
distmat <- as.matrix(dist(matrix(rnorm(100), 50, 2)))
nd <- null_moran(data, distmat, n_perm = 10L, seed = 1L)

```

null_spin_vasa	<i>Spin-test null models for brain maps</i>
----------------	---

Description

Generate spatially-constrained null distributions using spin-based permutation of spherical coordinates.

Usage

```
null_spin_vasa(  
  data,  
  coords,  
  n_perm = 1000L,  
  seed = NULL,  
  rotation = c("euler", "rodrigues")  
)
```

```
null_spin_hungarian(  
  data,  
  coords,  
  n_perm = 1000L,  
  seed = NULL,  
  rotation = c("euler", "rodrigues")  
)
```

Arguments

data	Numeric vector of brain map values.
coords	List with \$lh and \$rh matrices of spherical coordinates (n x 3 each).
n_perm	Integer number of null permutations to generate.
seed	Optional integer seed for reproducibility.
rotation	Rotation generation method: "euler" (ZYZ Euler angles, default, matches neuromaps Python) or "rodrigues" (Rodrigues axis-angle formula).

Value

A [null_distribution](#) object.

References

Alexander-Bloch AF et al. (2018) NeuroImage 175:111-120. doi:10.1016/j.neuroimage.2018.04.023
Vasa F et al. (2018) Cerebral Cortex 28:3293-3303. doi:10.1093/cercor/bhx195
Markello RD, Misisic B (2021) NeuroImage 236:118052. doi:10.1016/j.neuroimage.2021.118052

Examples

```
coords <- list(lh = matrix(rnorm(30), 10, 3), rh = matrix(rnorm(30), 10, 3))
data <- rnorm(20)
nd <- null_spin_vasa(data, coords, n_perm = 10L, seed = 1L)
```

parcellate

Parcellate brain map data

Description

High-level wrapper that reads data and parcellation from file paths or vectors, then aggregates vertices into parcels.

Usage

```
parcellate(data, parcellation, summary_func = mean)
```

Arguments

data	Numeric vector or file path to a GIFTI/NIfTI brain map.
parcellation	Integer vector of labels or file path to a GIFTI label file.
summary_func	Function to summarise each parcel (default: mean).

Value

Named numeric vector of parcel-level values.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
data <- c(1.0, 2.0, 3.0, 4.0)
labels <- c(1L, 1L, 2L, 2L)
parcellate(data, labels)
```

parcels_to_vertices *Map parcel data back to vertices*

Description

Expands parcel-level values to a vertex-level vector using parcellation labels.

Usage

```
parcels_to_vertices(parcel_data, labels, fill = NA_real_)
```

Arguments

parcel_data	Named numeric vector of parcel values (names match labels).
labels	Integer vector of parcel labels. 0 and NA are medial wall.
fill	Value for medial wall vertices (default: NA_real_).

Value

Numeric vector of length(labels).

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
parcel_data <- c("1" = 10, "2" = 20)
labels <- c(1L, 1L, 2L, 2L, 0L)
parcels_to_vertices(parcel_data, labels)
```

permtest_metric *Permutation test for any metric between brain maps*

Description

Computes a user-specified metric between two vectors and tests significance using either spatially-constrained null surrogates or simple random permutation.

Usage

```
permtest_metric(
  x,
  y,
  metric_func = stats::cor,
  n_perm = 1000L,
  seed = NULL,
  null_method = NULL,
  distmat = NULL,
  coords = NULL,
  parcellation = NULL,
  ...
)
```

Arguments

<code>x, y</code>	Numeric vectors.
<code>metric_func</code>	Function taking (<code>x</code> , <code>y</code>) and returning a scalar.
<code>n_perm</code>	Integer number of permutations.
<code>seed</code>	Optional integer seed for reproducibility.
<code>null_method</code>	Optional null model method passed to generate_nulls() . If NULL, uses simple random permutation.
<code>distmat</code>	Distance matrix (passed to generate_nulls() if needed).
<code>coords</code>	Coordinate list (passed to generate_nulls() if needed).
<code>parcellation</code>	Integer vector (passed to generate_nulls() if needed).
<code>...</code>	Additional arguments passed to generate_nulls() .

Value

List with `$observed`, `$null_values`, `$p_value`, and `$n_perm`.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
x <- rnorm(100)
y <- x + rnorm(100)
result <- permtest_metric(x, y, n_perm = 99L, seed = 1L)
result$observed
result$p_value
```

read_brain_map_values *Read vertex/voxel values from a brain map file*

Description

Reads GIFTI (.func.gii) or NIfTI (.nii.gz) files and returns the values as a numeric vector. Used internally by [compare_maps\(\)](#) when file paths are passed instead of numeric vectors.

Usage

```
read_brain_map_values(path)
```

Arguments

path Path to a .func.gii (GIFTI) or .nii.gz (NIfTI) file.

Value

A numeric vector of map values.

Examples

```
## Not run:
read_brain_map_values("cortical_thickness.func.gii")
read_brain_map_values("brain_volume.nii.gz")

## End(Not run)
```

resample_images *Resample brain maps for comparison*

Description

Aligns two brain maps into the same coordinate space and density before comparison. Supports multiple strategies for choosing the target space.

Usage

```
resample_images(
  src,
  trg,
  src_space = c("fsaverage", "fsLR"),
  trg_space = c("fsaverage", "fsLR"),
  strategy = c("downsample_only", "transform_to_src", "transform_to_trg",
    "transform_to_alt"),
  alt_space = NULL,
```

```

    alt_density = NULL,
    hemisphere = c("left", "right"),
    area_surf_current = NULL,
    area_surf_new = NULL,
    wb_path = NULL,
    verbose = TRUE
)

```

Arguments

src	Character, file path to the source GIFTI.
trg	Character, file path to the target GIFTI.
src_space	Source coordinate space ("fsaverage" or "fsLR").
trg_space	Target coordinate space ("fsaverage" or "fsLR").
strategy	Resampling strategy. One of "downsample_only", "transform_to_src", "transform_to_trg", or "transform_to_alt".
alt_space	Alternative space for "transform_to_alt" strategy.
alt_density	Alternative density for "transform_to_alt" strategy.
hemisphere	Which hemispheres: "left", "right", or both.
area_surf_current	Path to a current-resolution area-correction surface (e.g. midthickness). Passed to transform_to_space() .
area_surf_new	Path to a target-resolution area-correction surface. Passed to transform_to_space() .
wb_path	Path to wb_command executable.
verbose	Logical, print progress messages.

Value

List with \$src and \$trg file paths in the aligned space.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```

## Not run:
resample_images("src.func.gii", "trg.func.gii",
  src_space = "fsaverage", trg_space = "fsaverage"
)

## End(Not run)

```

transform_to_space *Transform brain maps between coordinate spaces*

Description

Resamples GIFTI surface files between fsaverage and fsLR coordinate spaces using Connectome Workbench via ciftiTools.

Usage

```
transform_to_space(
    paths,
    target_space = c("fsLR", "fsaverage"),
    target_density = "32k",
    hemisphere = c("left", "right"),
    method = c("adaptive", "barycentric"),
    area_surf_current = NULL,
    area_surf_new = NULL,
    wb_path = NULL,
    verbose = TRUE
)
```

Arguments

paths	Character vector of GIFTI file paths to transform.
target_space	Target coordinate space: "fsLR" or "fsaverage".
target_density	Target mesh density (e.g., "32k", "164k").
hemisphere	Which hemispheres to transform: "left", "right", or both.
method	Resampling method: "adaptive" (default) or "barycentric".
area_surf_current	Path to the current-resolution area-correction surface (e.g. midthickness). Recommended when method = "adaptive" for proper vertex-area correction (matches neuromaps Python behaviour).
area_surf_new	Path to the target-resolution area-correction surface. If NULL and area_surf_current is provided, ciftiTools resamples it barycentrically.
wb_path	Path to wb_command executable. If NULL, auto-detected via ciftiTools.
verbose	Logical, print progress messages.

Value

Character vector of transformed file paths.

References

Robinson EC et al. (2014) NeuroImage 100:414-426. doi:10.1016/j.neuroimage.2014.07.033
 Robinson EC et al. (2018) NeuroImage 167:150-165. doi:10.1016/j.neuroimage.2017.10.037

Examples

```
## Not run:  
transform_to_space("map.func.gii", target_space = "fsLR")  
  
## End(Not run)
```

unparcellate

Unparcellate brain map data

Description

Inverse of [parcellate\(\)](#): maps parcel-level values back to vertices.

Usage

```
unparcellate(parcel_data, parcellation, fill = NA_real_)
```

Arguments

parcel_data	Named numeric vector of parcel values.
parcellation	Integer vector of labels or file path to a GIFTI label file.
fill	Value for medial wall vertices (default: NA_real_).

Value

Numeric vector of vertex-level values.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
parcel_data <- c("1" = 10, "2" = 20)  
labels <- c(1L, 1L, 2L, 2L, 0L)  
unparcellate(parcel_data, labels)
```

vertex_areas *Compute per-vertex surface areas*

Description

Each triangle distributes one-third of its area to each of its three vertices. Triangle area is computed via the cross-product formula.

Usage

```
vertex_areas(vertices, faces)
```

Arguments

vertices Numeric matrix (n x 3) of vertex coordinates.
 faces Integer matrix (m x 3) of face indices (1-indexed).

Value

Numeric vector of length nrow(vertices).

Examples

```
vertices <- matrix(c(0, 1, 0, 0, 0, 1, 0, 0, 0), nrow = 3, byrow = TRUE)
faces <- matrix(c(1L, 2L, 3L), nrow = 1)
vertex_areas(vertices, faces)
```

vertices_to_parcel *Aggregate vertex data into parcels*

Description

Summarises vertex-level data by parcellation labels.

Usage

```
vertices_to_parcel(data, labels, summary_func = mean)
```

Arguments

data Numeric vector of vertex-level values.
 labels Integer vector of parcel labels. 0 and NA are treated as medial wall and excluded.
 summary_func Function to summarise each parcel (default: [mean](#)).

Value

Named numeric vector of parcel-level values.

References

Markello RD et al. (2022) Nature Methods 19:1472-1480. doi:10.1038/s41592-022-01625-w

Examples

```
data <- c(1.0, 2.0, 3.0, 4.0)
labels <- c(1L, 1L, 2L, 2L)
vertices_to_parcel(data, labels)
```

Index

annot_to_gifti, 2
as.matrix.null_distribution
 (null_distribution), 17

check_wb_command, 3
clear_neuromaps_cache, 4
compare_maps, 4
compare_maps(), 23

fetch_neuromaps_annotation, 5
fetch_neuromaps_annotation(), 4, 11
fsmorph_to_gifti, 6

generate_nulls, 7
generate_nulls(), 5, 22
get_parcel_centroids, 8
get_surface_distance, 9
grepl(), 11

make_surf_graph, 10
mean, 20, 27

neuromaps_available, 11
neuromaps_available(), 4
new_null_distribution
 (null_distribution), 17
null_alexander_bloch, 12
null_baum, 13
null_burt2018, 14
null_burt2020, 14
null_cornblath, 16
null_distribution, 5, 8, 12–16, 17, 18, 19
null_moran, 18
null_spin_hungarian (null_spin_vasa), 19
null_spin_vasa, 19

parcellate, 20
parcellate(), 26
parcels_to_vertices, 21
permtest_metric, 21

plot.null_distribution
 (null_distribution), 17
print.neuromaps_enhanced_comparison
 (compare_maps), 4
print.null_distribution
 (null_distribution), 17

read_brain_map_values, 23
resample_images, 23

summary.null_distribution
 (null_distribution), 17

transform_to_space, 25
transform_to_space(), 24

unparcellate, 26

vertex_areas, 27
vertices_to_parcels, 27