

Package ‘nmw’

April 7, 2026

Version 0.2.0

Title Understanding Nonlinear Mixed Effects Modeling for Population Pharmacokinetics

Description This shows how NONMEM(R) software works. NONMEM's classical estimation methods like 'First Order(FO) approximation', 'First Order Conditional Estimation(FOCE)', and 'Laplacian approximation' are explained. Additionally, provides functions for post-run processing of NONMEM output files, generating comprehensive PDF diagnostic reports including objective function value analysis, parameter estimates, prediction diagnostics, residual diagnostics, empirical Bayes estimate (EBE) analysis, input data summary, and individual pharmacokinetic parameter distributions.

Depends R (>= 3.5.0), numDeriv

Imports MASS, grDevices, graphics, stats, utils

ByteCompile yes

License GPL-3

Copyright 2017-, Kyun-Seop Bae

Author Kyun-Seop Bae [aut, cre]

Maintainer Kyun-Seop Bae <k@acr.kr>

URL <https://cran.r-project.org/package=nmw>

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

NeedsCompilation no

RoxygenNote 7.3.3

Repository CRAN

Date/Publication 2026-04-07 05:20:08 UTC

Contents

nmw-package	3
AddCox	5
AddDoNoTaLD	6
AddPage	6
BtwTagMat	7
BtwTagVals	8
ClosePDF	8
CombDmExPc	8
CovStep	9
DxPlotPost	10
EBEpair	11
EstStep	11
ExpandDoseHist	12
GetAICc	12
GetCountEps	13
GetCountEta	13
GetCountObs	13
GetCountPara	14
GetEstMethod	14
GetOFV	14
InitStep	15
LogDV	17
LogDV2	17
MinSuccess	18
mlr2	18
NMIDStat	19
NMVarStat	19
nmw_report_ebe	20
nmw_report_indipk	20
nmw_report_input	21
nmw_report_ofv	21
nmw_report_output	21
nmw_report_param	22
nmw_report_pred	22
nmw_report_resid	22
nmw_run	23
Outline	23
ParseOut	24
PrepPDF	24
PrinMTxt	25
PrinTxt	25
RemoveNA	26
ResTest	26
run.test.nm	27
SESuccess	27
SumOut	28

TabStep	28
TrimOut	29

Index	30
--------------	-----------

nmw-package	<i>Understanding Nonlinear Mixed Effects Modeling for Population Pharmacokinetics</i>
-------------	---

Description

This shows how NONMEM(R) <<http://www.iconplc.com/innovation/nonmem/>> software works. Additionally, provides functions for post-run processing of NONMEM output files, generating comprehensive PDF diagnostic reports.

Details

This package explains 'First Order(FO) approximation' method, 'First Order Conditional Estimation(FOCE)' method, and 'Laplacian(LAPL)' method of NONMEM software. It also provides post-run processing functions including PDF diagnostic reports for OFV analysis, parameter estimates, prediction diagnostics, residual diagnostics, EBE analysis, input data summary, and individual PK parameter distributions.

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. NONMEM Users guide
2. Wang Y. Derivation of various NONMEM estimation methods. J Pharmacokinet Pharmacodyn. 2007.
3. Kang D, Bae K, Houk BE, Savic RM, Karlsson MO. Standard Error of Empirical Bayes Estimate in NONMEM(R) VI. K J Physiol Pharmacol. 2012.
4. Kim M, Yim D, Bae K. R-based reproduction of the estimation process hidden behind NONMEM Part 1: First order approximation method. 2015.
5. Bae K, Yim D. R-based reproduction of the estimation process hidden behind NONMEM Part 2: First order conditional estimation. 2016.

Examples

```
DataAll = Theoph
colnames(DataAll) = c("ID", "BWT", "DOSE", "TIME", "DV")
DataAll[, "ID"] = as.numeric(as.character(DataAll[, "ID"]))
```

```
nTheta = 3
nEta = 3
nEps = 2
```

```

THETAinit = c(2, 50, 0.1)
OMinit = matrix(c(0.2, 0.1, 0.1, 0.1, 0.2, 0.1, 0.1, 0.1, 0.2), nrow=nEta, ncol=nEta)
SGinit = diag(c(0.1, 0.1))

LB = rep(0, nTheta) # Lower bound
UB = rep(1000000, nTheta) # Upper bound

FGD = deriv(~DOSE/(TH2*exp(ETA2))*TH1*exp(ETA1)/(TH1*exp(ETA1) - TH3*exp(ETA3))*
            (exp(-TH3*exp(ETA3)*TIME)-exp(-TH1*exp(ETA1)*TIME)),
            c("ETA1", "ETA2", "ETA3"),
            function.arg=c("TH1", "TH2", "TH3", "ETA1", "ETA2", "ETA3", "DOSE", "TIME"),
            func=TRUE, hessian=TRUE)
H = deriv(~F + F*EPS1 + EPS2, c("EPS1", "EPS2"), function.arg=c("F", "EPS1", "EPS2"), func=TRUE)

PRED = function(THETA, ETA, DATAi)
{
  FGDres = FGD(THETA[1], THETA[2], THETA[3], ETA[1], ETA[2], ETA[3], DOSE=320, DATAi[, "TIME"])
  Gres = attr(FGDres, "gradient")
  Hres = attr(H(FGDres, 0, 0), "gradient")

  if (e$METHOD == "LAPL") {
    Dres = attr(FGDres, "hessian")
    Res = cbind(FGDres, Gres, Hres, Dres[,1,1], Dres[,2,1], Dres[,2,2], Dres[,3,])
    colnames(Res) = c("F", "G1", "G2", "G3", "H1", "H2", "D11", "D21", "D22", "D31", "D32", "D33")
  } else {
    Res = cbind(FGDres, Gres, Hres)
    colnames(Res) = c("F", "G1", "G2", "G3", "H1", "H2")
  }
  return(Res)
}

##### First Order Approximation Method # Commented out for the CRAN CPU time
#InitStep(DataAll, THETAinit=THETAinit, OMinit=OMinit, SGinit=SGinit, LB=LB, UB=UB,
#          Pred=PRED, METHOD="ZERO")
#(EstRes = EstStep())          # 4 sec
#(CovRes = CovStep())          # 2 sec
#PostHocEta() # Using e$FinalPara from EstStep()
#TabStep()

##### First Order Conditional Estimation with Interaction Method
#InitStep(DataAll, THETAinit=THETAinit, OMinit=OMinit, SGinit=SGinit, LB=LB, UB=UB,
#          Pred=PRED, METHOD="COND")
#(EstRes = EstStep())          # 2 min
#(CovRes = CovStep())          # 1 min
#get("EBE", envir=e)
#TabStep()

##### Laplacian Approximation with Interaction Method
#InitStep(DataAll, THETAinit=THETAinit, OMinit=OMinit, SGinit=SGinit, LB=LB, UB=UB,
#          Pred=PRED, METHOD="LAPL")
#(EstRes = EstStep())          # 4 min
#(CovRes = CovStep())          # 1 min

```

```
#get("EBE", envir=e)
#TabStep()
```

AddCox*Add a Covariate Column to an Existing NONMEM dataset*

Description

A new covariate column can be added to an existing NONMEM dataset.

Usage

```
AddCox(nmData, coxData, coxCol, dateCol = "DATE", idCol = "ID")
```

Arguments

nmData	an existing NONMEM dataset
coxData	a data table containing a covariate column
coxCol	the covariate column name in the coxData table
dateCol	date column name in the NONMEM dataset and the covariate data table
idCol	ID column name in the NONMEM dataset and the covariate data table

Details

It first carry forward for the missing data. If NA is remained, it carry backward.

Value

A new NONMEM dataset containing the covariate column

Author(s)

Kyun-Seop Bae <k@acr.kr>

 AddDoNoTaLD

Add Dose Number, Time of Latest Dose, and Time after Latest Dose

Description

Adds DoNo (Dosing Occasion Number), ToLD (Time of Latest Dose), and TaLD (Time after Latest Dose) columns to a NONMEM dataset.

Usage

```
AddDoNoTaLD(
  NMData,
  ID = "ID",
  TIME = "TIME",
  AMT = "AMT",
  II = "II",
  ADDL = "ADDL",
  MDV = "MDV"
)
```

Arguments

NMData	data.frame of NONMEM dataset
ID	character, column name for subject ID
TIME	character, column name for time
AMT	character, column name for dose amount
II	character, column name for interdose interval
ADDL	character, column name for additional doses
MDV	character, column name for missing dependent variable flag

Value

data.frame with DoNo, ToLD, TaLD columns added

 AddPage

Add a New Page to PDF

Description

Creates a new page in the PDF output with optional headers and footers.

Usage

```
AddPage(
  Cex = 0.8,
  Header1 = "",
  Header2 = "",
  Header3 = "",
  Footer1 = "",
  Footer2 = "",
  Footer3 = "",
  PrintRowNum = FALSE,
  StartRowNum = 1
)
```

Arguments

Cex	numeric, character expansion factor (0.8 or 0.6)
Header1	character, left header
Header2	character, center header
Header3	character, right header
Footer1	character, left footer
Footer2	character, center footer
Footer3	character, right footer
PrintRowNum	logical, whether to print row numbers
StartRowNum	integer, starting row number

 BtwTagMat

Extract Matrix from NONMEM XML Output

Description

Parses NONMEM XML output to extract omega or sigma matrices.

Usage

```
BtwTagMat(Tag, RawRead, nRow)
```

Arguments

Tag	character, the tag name (e.g., "omega", "sigma")
RawRead	character vector of XML lines
nRow	integer, dimension of the matrix

Value

numeric matrix

BtwTagVals	<i>Extract Vector of Values Between XML Tags</i>
------------	--

Description

Parses NONMEM XML output to extract theta, omega, or sigma vectors.

Usage

```
BtwTagVals(Tag, RawRead)
```

Arguments

Tag	character, the tag name (e.g., "nm:theta")
RawRead	character vector of XML lines

Value

numeric vector of values

ClosePDF	<i>Close PDF Output</i>
----------	-------------------------

Description

Closes the current PDF device.

Usage

```
ClosePDF()
```

CombDmExPc	<i>Combine the demographics(DM), dosing(EX), and DV(PC) tables into a new NONMEM dataset</i>
------------	--

Description

A new NONMEM dataset can be created from the demographics, dosing, and DV tables.

Usage

```
CombDmExPc(dm, ex, pc)
```

Arguments

dm	A demographics table. It should contain a row per subject.
ex	An exposure table. Drug administration (dosing) history table.
pc	A DV(dependent variable) or PC(drug concentration) table

Details

Combining a demographics, a dosing, and a concentration table can produce a new NONMEM dataset.

Value

A new NONMEM dataset

Author(s)

Kyun-Seop Bae <k@acr.kr>

CovStep

Covariance Step

Description

It calculates standard errors and various variance matrices with the e\$FinalPara after estimation step.

Usage

CovStep()

Details

Because EstStep uses nonlinear optimization, covariance step is separated from estimation step. It calculates variance-covariance matrix of estimates in the original scale.

Value

Time	consumed time
Standard Error	standard error of the estimates in the order of theta, omega, and sigma
Covariance Matrix of Estimates	covariance matrix of estimates in the order of theta, omega, and sigma. This is inverse(R) x S x inverse(R) by default.
Correlation Matrix of Estimates	correlation matrix of estimates in the order of theta, omega, and sigma
Inverse Covariance Matrix of Estimates	inverse covariance matrix of estimates in the order of theta, omega, and sigma

Eigen Values	eigen values of covariance matrix
R Matrix	R matrix of NONMEM, the second derivative of log likelihood function with respect to estimation parameters
S Matrix	S matrix of NONMEM, sum of individual cross-product of the first derivative of log likelihood function with respect to estimation parameters

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

NONMEM Users Guide

See Also

[EstStep](#), [InitStep](#)

Examples

```
# Only after InitStep and EstStep
#CovStep()
```

DxPlotPost

Diagnostic Plot for Post-Processing

Description

Creates spaghetti-style diagnostic plots with individual ID labels.

Usage

```
DxPlotPost(x, y, mat, xlabel, ylabel, smooth, xlim = "", ylim = "", Log = "")
```

Arguments

x	numeric vector, x-axis values
y	numeric vector, y-axis values
mat	data.frame with an ID column
xlabel	character, x-axis label
ylabel	character, y-axis label
smooth	character, "T" for lowess smoothing, "F" for identity line
xlim	numeric vector of length 2, x-axis limits
ylim	numeric vector of length 2, y-axis limits
Log	character, log transformation for axes (e.g., "y")

EBEpair	<i>EBE Pair Plot</i>
---------	----------------------

Description

Creates pairs plot of ETAs vs covariates with histograms and correlations.

Usage

```
EBEpair(tabEta, RunNumber, each = FALSE)
```

Arguments

tabEta	data.frame with ID, covariates, and ETA columns
RunNumber	character, model/run identifier
each	logical, if TRUE creates separate plots per covariate

EstStep	<i>Estimation Step</i>
---------	------------------------

Description

This estimates upon the conditions with InitStep.

Usage

```
EstStep()
```

Details

It does not have arguments. All necessary arguments are stored in the `e` environment. It assumes "INTERACTION" between eta and epsilon for "COND" and "LAPL" options. The output is basically same to NONMEM output.

Value

Initial OFV	initial value of the objective function
Time	time consumed for this step
Optim	the raw output from <code>optim</code> function
Final Estimates	final estimates in the original scale

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

NONMEM Users Guide

See Also

[InitStep](#)

Examples

```
# Only After InitStep
#EstStep()
```

ExpandDoseHist	<i>Expand Dose History with ADDL/II Records</i>
----------------	---

Description

Expands compressed dosing records (ADDL/II) into individual dose records.

Usage

```
ExpandDoseHist(DoseHistTab)
```

Arguments

DoseHistTab data.frame with columns TIME, AMT, II, ADDL

Value

data.frame with expanded dose records

GetAICc	<i>Get Corrected AIC (AICc)</i>
---------	---------------------------------

Description

Get Corrected AIC (AICc)

Usage

```
GetAICc()
```

Value

numeric, the corrected AIC value

GetCountEps	<i>Get Count of Epsilons</i>
-------------	------------------------------

Description

Get Count of Epsilons

Usage

GetCountEps()

Value

integer, number of epsilon parameters

GetCountEta	<i>Get Count of Etas</i>
-------------	--------------------------

Description

Get Count of Etas

Usage

GetCountEta()

Value

integer, number of eta parameters

GetCountObs	<i>Get Count of Observations</i>
-------------	----------------------------------

Description

Get Count of Observations

Usage

GetCountObs()

Value

integer, total number of observation records

GetCountPara	<i>Get Count of Parameters</i>
--------------	--------------------------------

Description

Get Count of Parameters

Usage

GetCountPara()

Value

integer, total number of estimated parameters

GetEstMethod	<i>Get Estimation Method</i>
--------------	------------------------------

Description

Identifies the estimation method from the .ext file header.

Usage

GetEstMethod()

Value

character, abbreviation of the estimation method

GetOFV	<i>Get Objective Function Value</i>
--------	-------------------------------------

Description

Retrieves the final OFV from the .ext file in the current directory.

Usage

GetOFV()

Value

numeric, the objective function value

InitStep	<i>Initialization Step</i>
----------	----------------------------

Description

It receives parameters for the estimation and stores them into e environment.

Usage

```
InitStep(DataAll, THETAinit, OMinit, SGinit, LB, UB, Pred, METHOD)
```

Arguments

DataAll	Data for all subjects. It should contain columns which Pred function uses.
THETAinit	Theta initial values
OMinit	Omega matrix initial values
SGinit	Sigma matrix initial values
LB	Lower bounds for theta vector
UB	Upper bounds for theta vector
Pred	Prediction function name
METHOD	one of the estimation methods "ZERO", "COND", or "LAPL"

Details

Prediction function should return not only prediction values(F or IPRED) but also G (first derivative with respect to etas) and H (first derivative of Y with respect to epsilon). For the "LAPL", prediction function should return second derivative with respect to eta also. "INTERACTION" is TRUE for "COND" and "LAPL" option, and FALSE for "ZERO". Omega matrix should be full block one. Sigma matrix should be diagonal one.

Value

This does not return values, but stores necessary values into the environment e.

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

NONMEM Users Guide

Examples

```

DataAll = Theoph
colnames(DataAll) = c("ID", "BWT", "DOSE", "TIME", "DV")
DataAll[, "ID"] = as.numeric(as.character(DataAll[, "ID"]))

nTheta = 3
nEta = 3
nEps = 2

THETAinit = c(2, 50, 0.1) # Initial estimate
OMinit = matrix(c(0.2, 0.1, 0.1, 0.1, 0.2, 0.1, 0.1, 0.1, 0.2), nrow=nEta, ncol=nEta)
OMinit
SGinit = diag(c(0.1, 0.1))
SGinit

LB = rep(0, nTheta) # Lower bound
UB = rep(1000000, nTheta) # Upper bound

FGD = deriv(~DOSE/(TH2*exp(ETA2))*TH1*exp(ETA1)/(TH1*exp(ETA1) - TH3*exp(ETA3))*
            (exp(-TH3*exp(ETA3)*TIME)-exp(-TH1*exp(ETA1)*TIME)),
            c("ETA1", "ETA2", "ETA3"),
            function.arg=c("TH1", "TH2", "TH3", "ETA1", "ETA2", "ETA3", "DOSE", "TIME"),
            func=TRUE, hessian=TRUE)
H = deriv(~F + F*EPS1 + EPS2, c("EPS1", "EPS2"), function.arg=c("F", "EPS1", "EPS2"), func=TRUE)

PRED = function(THETA, ETA, DATAi)
{
  FGDres = FGD(THETA[1], THETA[2], THETA[3], ETA[1], ETA[2], ETA[3], DOSE=320, DATAi[, "TIME"])
  Gres = attr(FGDres, "gradient")
  Hres = attr(H(FGDres, 0, 0), "gradient")

  if (e$METHOD == "LAPL") {
    Dres = attr(FGDres, "hessian")
    Res = cbind(FGDres, Gres, Hres, Dres[,1,1], Dres[,2,1], Dres[,2,2], Dres[,3,])
    colnames(Res) = c("F", "G1", "G2", "G3", "H1", "H2", "D11", "D21", "D22", "D31", "D32", "D33")
  } else {
    Res = cbind(FGDres, Gres, Hres)
    colnames(Res) = c("F", "G1", "G2", "G3", "H1", "H2")
  }
  return(Res)
}

##### First Order Approximation Method
InitStep(DataAll, THETAinit=THETAinit, OMinit=OMinit, SGinit=SGinit, LB=LB, UB=UB,
         Pred=PRED, METHOD="ZERO")

##### First Order Conditional Estimation with Interaction Method
InitStep(DataAll, THETAinit=THETAinit, OMinit=OMinit, SGinit=SGinit, LB=LB, UB=UB,
         Pred=PRED, METHOD="COND")

##### Laplacian Approximation with Interaction Method
InitStep(DataAll, THETAinit=THETAinit, OMinit=OMinit, SGinit=SGinit, LB=LB, UB=UB,

```

```
Pred=PRED, METHOD="LAPL")
```

 LogDV

Check if Model Uses Log-Transformed DV (from Control File)

Description

Check if Model Uses Log-Transformed DV (from Control File)

Usage

```
LogDV(CtlFileName)
```

Arguments

CtlFileName character, path to NONMEM control file

Value

logical, TRUE if LOG(F) is found after \$PRED or \$ERROR

 LogDV2

Check if Model Uses Log-Transformed DV (from FSUBS)

Description

Check if Model Uses Log-Transformed DV (from FSUBS)

Usage

```
LogDV2()
```

Value

logical, TRUE if LOG(F) is found after SUBROUTINE PRED or ERROR in FSUBS

MinSuccess	<i>Check Minimization Success</i>
------------	-----------------------------------

Description

Check Minimization Success

Usage

```
MinSuccess()
```

Value

logical, TRUE if minimization was successful

mlr2	<i>Multiple Linear Regression with Influence Diagnostics</i>
------	--

Description

Performs multiple linear regression and computes influence diagnostics including DFFITS, DFBE-TAS, Cook's Distance, COVRATIO, and R-Student.

Usage

```
mlr2(y, x.raw, standardize = 0)
```

Arguments

y	numeric vector of response
x.raw	data.frame of predictors
standardize	integer, standardization method (0=none, 1=center, 2=scale by mean, 3=z-score)

Value

list with model estimates and influence diagnostics

NMIDStat	<i>NONMEM Individual (ID) Statistics</i>
----------	--

Description

Computes per-subject statistics including record counts, DV counts, dosing information, and sorting checks.

Usage

```
NMIDStat(NMTable)
```

Arguments

NMTable data.frame of NONMEM data

Value

list with IDStat data.frame, sortedID logical, sortedDT logical

NMVarStat	<i>NONMEM Variable Statistics</i>
-----------	-----------------------------------

Description

Computes statistics for each variable in a NONMEM dataset including counts of NA, zero, positive values, unique values, and functional dependency checks.

Usage

```
NMVarStat(NMTable)
```

Arguments

NMTable data.frame of NONMEM data

Value

matrix with variable statistics

nmw_report_ebe	<i>Generate EBE Diagnostics Report (S5-EBE.PDF)</i>
----------------	---

Description

Generates a PDF report with empirical Bayes estimate (EBE) analysis including ETA distributions, shrinkage, covariate relationships, correlations, and multiple linear regression with influence diagnostics.

Usage

```
nmw_report_ebe(run_dir = getwd())
```

Arguments

run_dir character, path to the NONMEM run directory (default: current directory)

nmw_report_indipk	<i>Generate Individual PK Parameter Report (SC-IndiPK.PDF)</i>
-------------------	--

Description

Generates a PDF report with individual PK parameter distributions including summary statistics, histograms, and QQ plots.

Usage

```
nmw_report_indipk(run_dir = getwd())
```

Arguments

run_dir character, path to the NONMEM run directory (default: current directory)

nmw_report_input	<i>Generate Input Data Summary Report (SA-Input.PDF)</i>
------------------	--

Description

Generates a PDF report with input data validation including individuals with no dosing/DV, duplicate records, and summary statistics.

Usage

```
nmw_report_input(run_dir = getwd())
```

Arguments

run_dir	character, path to the NONMEM run directory (default: current directory)
---------	--

nmw_report_ofv	<i>Generate OFV Diagnostic Report (SI-OFV.PDF)</i>
----------------	--

Description

Generates a PDF report with objective function value diagnostics including total OFV, AICc, BIC, individual OFV per DV summary, and gradient analysis.

Usage

```
nmw_report_ofv(run_dir = getwd())
```

Arguments

run_dir	character, path to the NONMEM run directory (default: current directory)
---------	--

nmw_report_output	<i>Generate NONMEM Output Report (SB-Output.PDF)</i>
-------------------	--

Description

Includes the NONMEM PRINT.OUT file content in a PDF report.

Usage

```
nmw_report_output(run_dir = getwd())
```

Arguments

run_dir	character, path to the NONMEM run directory (default: current directory)
---------	--

nmw_report_param	<i>Generate Parameter Estimates Report (S2-Parameters.PDF)</i>
------------------	--

Description

Generates a PDF report with theta, omega, and sigma parameter estimates, standard errors, confidence intervals, and significance flags.

Usage

```
nmw_report_param(run_dir = getwd())
```

Arguments

run_dir	character, path to the NONMEM run directory (default: current directory)
---------	--

nmw_report_pred	<i>Generate Prediction Diagnostics Report (S3-Predictions.PDF)</i>
-----------------	--

Description

Generates a PDF report with spaghetti plots, DV vs PRED/IPRE, and individual fitting curves.

Usage

```
nmw_report_pred(run_dir = getwd())
```

Arguments

run_dir	character, path to the NONMEM run directory (default: current directory)
---------	--

nmw_report_resid	<i>Generate Residual Diagnostics Report (S4-Residuals.PDF)</i>
------------------	--

Description

Generates a PDF report with WRES, CWRES, IWRES diagnostics including scatter plots, histograms, normality tests, binomial count tests, and individual residual curves with run tests.

Usage

```
nmw_report_resid(run_dir = getwd())
```

Arguments

run_dir	character, path to the NONMEM run directory (default: current directory)
---------	--

nmw_run

*Run All NONMEM Post-Processing Reports***Description**

Generates all diagnostic PDF reports for a NONMEM run in sequence: S1-OFV, S2-Parameters, S3-Predictions, S4-Residuals, S5-EBE, SA-Input, SB-Output, SC-IndiPK.

Usage

```
nmw_run(
  run_dir = getwd(),
  reports = c("ofv", "param", "pred", "resid", "ebe", "input", "output", "indipk")
)
```

Arguments

`run_dir` character, path to the NONMEM run directory (default: current directory)

`reports` character vector, which reports to generate. Options: "ofv", "param", "pred", "resid", "ebe", "input", "output", "indipk". Default is all reports.

Examples

```
## Not run:
# Generate all reports
nmw_run("/path/to/nonmem/run/directory")

# Generate only OFV and parameter reports
nmw_run("/path/to/run", reports = c("ofv", "param"))

## End(Not run)
```

Outline

*Draw Model Development Flow Diagram***Description**

Creates a graphical model development flow diagram from SumOut results.

Usage

```
Outline(MDL, MDLName, out.start = "0", out.end = "zzzzzzzz", Target = "PDF")
```

Arguments

MDL	data.frame from SumOut
MDLName	character, model development name for title
out.start	character, filter start
out.end	character, filter end
Target	character, "PDF" or other

ParseOut	<i>Parse Value After Tag from NONMEM Output</i>
----------	---

Description

Extracts the value following a tag string (after the colon) in NONMEM output lines.

Usage

```
ParseOut(TagString, RawRead)
```

Arguments

TagString	character, the tag to search for
RawRead	character vector of lines from NONMEM output

Value

character, the value after the tag

PrepPDF	<i>Prepare PDF Output</i>
---------	---------------------------

Description

Opens a PDF device for NONMEM report generation.

Usage

```
PrepPDF(FileName, Paper = "letter", FontFamily = "Courier")
```

Arguments

FileName	character, output PDF filename
Paper	character, paper size (default "letter")
FontFamily	character, font family (default "Courier")

PrinMTxt	<i>Print Multiple Lines of Text</i>
----------	-------------------------------------

Description

Prints a character vector of text lines across multiple pages as needed.

Usage

```
PrinMTxt(
  MTxt,
  Cex = 0.8,
  Header1 = "",
  Header2 = "",
  Header3 = "",
  Footer1 = "",
  Footer2 = "",
  Footer3 = "",
  PrintRowNum = FALSE
)
```

Arguments

MTxt	character vector of text lines
Cex	numeric, character expansion factor
Header1	character, left header
Header2	character, center header
Header3	character, right header
Footer1	character, left footer
Footer2	character, center footer
Footer3	character, right footer
PrintRowNum	logical, whether to print row numbers

PrinTxt	<i>Print Text at Position</i>
---------	-------------------------------

Description

Prints text at a specific row and column position on the PDF page.

Usage

```
PrinTxt(Row, Col, Text, Cex = 0.8)
```

Arguments

Row	numeric, row position
Col	numeric, column position
Text	character, text to print
Cex	numeric, character expansion factor

RemoveNA	<i>Remove Rows with NA Values</i>
----------	-----------------------------------

Description

Remove Rows with NA Values

Usage

```
RemoveNA(RawData)
```

Arguments

RawData	data.frame
---------	------------

Value

data.frame with rows containing NA removed

ResTest	<i>Residual Count Test Using Binomial Distribution</i>
---------	--

Description

Tests whether residual counts at various Z-value thresholds follow expected binomial distributions.

Usage

```
ResTest(
  ResTab,
  TestCols = c("WRES", "CWRE", "IWRE"),
  ZVals = c(0, 1, 2, 3),
  PctVals = c(0.005, 0.01, 0.025, 0.05, 0.1, 0.2, 0.3, 0.4, 0.5)
)
```

Arguments

ResTab	data.frame with residual columns
TestCols	character vector of column names to test
ZVals	numeric vector of Z-value thresholds
PctVals	numeric vector of percentile values

Value

matrix of test results

run.test.nm	<i>Runs Test for NONMEM Residuals</i>
-------------	---------------------------------------

Description

Performs a runs test on residuals. Zeros are omitted.

Usage

```
run.test.nm(RES)
```

Arguments

RES	numeric vector of residuals
-----	-----------------------------

Value

numeric, two-sided p-value

SESuccess	<i>Check Standard Error Success</i>
-----------	-------------------------------------

Description

Check Standard Error Success

Usage

```
SESuccess()
```

Value

logical, TRUE if standard errors were computed successfully

SumOut	<i>Summarize Multiple NONMEM Runs</i>
--------	---------------------------------------

Description

Scans subdirectories matching RunExt and collects summary metrics for model development flow analysis.

Usage

```
SumOut(FileExt = ".CTL", RunExt = ".R75", OutExt = ".OUT")
```

Arguments

FileExt	character, control file extension
RunExt	character, run folder extension
OutExt	character, output file extension

Value

data.frame with summary of all runs

TabStep	<i>Table Step</i>
---------	-------------------

Description

This produces standard table.

Usage

```
TabStep()
```

Details

It does not have arguments. All necessary arguments are stored in the e environment. This is similar to other standard results table.

Value

A table with ID, TIME, DV, PRED, RES, WRES, derivatives of G and H. If the estimation method is other than 'ZERO' (First-order approximation), it includes CWRES, CIPREDI (formerly IPRED), CIRESI (formerly IRES).

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

NONMEM Users Guide

See Also

[EstStep](#)

Examples

```
# Only After EstStep
#TabStep()
```

TrimOut

Trimming and beautifying NONMEM original OUTPUT file

Description

TrimOut removes unnecessary parts from NONMEM original OUTPUT file.

Usage

```
TrimOut(inFile, outFile="PRINT.OUT")
```

Arguments

inFile	NONMEM original untidy OUTPUT file name
outFile	Output file name to be written

Details

NONMEM original OUTPUT file contains unnecessary parts such as CONTROL file content, Start/End Time, License Info, Print control characters such as "+", "0", "1". This function trims those.

Value

outFile will be written in the current working folder or designated folder. This returns TRUE if the process was smooth.

Author(s)

Kyun-Seop Bae <k@acr.kr>

Index

- * **Covariance Step**
 - CovStep, [9](#)
 - * **Data Preparation**
 - AddCox, [5](#)
 - CombDmExPc, [8](#)
 - * **Estimation Step**
 - EstStep, [11](#)
 - * **Initialization Step**
 - InitStep, [15](#)
 - * **NONMEM OUTPUT**
 - TrimOut, [29](#)
 - * **Nonlinear Mixed Effects Modeling**
 - nmw-package, [3](#)
 - * **Population Pharmacokinetics**
 - nmw-package, [3](#)
 - * **Tabulation Step**
 - TabStep, [28](#)
- AddCox, [5](#)
AddDoNoTaLD, [6](#)
AddPage, [6](#)
- BtwTagMat, [7](#)
BtwTagVals, [8](#)
- ClosePDF, [8](#)
CombDmExPc, [8](#)
CovStep, [9](#)
- DxPlotPost, [10](#)
- EBEpair, [11](#)
EstStep, [10](#), [11](#), [29](#)
ExpandDoseHist, [12](#)
- GetAICc, [12](#)
GetCountEps, [13](#)
GetCountEta, [13](#)
GetCountObs, [13](#)
GetCountPara, [14](#)
GetEstMethod, [14](#)
- GetOFV, [14](#)
- InitStep, [10](#), [12](#), [15](#)
- LogDV, [17](#)
LogDV2, [17](#)
- MinSuccess, [18](#)
mlr2, [18](#)
- NMIDStat, [19](#)
NMVarStat, [19](#)
nmw (nmw-package), [3](#)
nmw-package, [3](#)
nmw_report_ebe, [20](#)
nmw_report_indipk, [20](#)
nmw_report_input, [21](#)
nmw_report_ofv, [21](#)
nmw_report_output, [21](#)
nmw_report_param, [22](#)
nmw_report_pred, [22](#)
nmw_report_resid, [22](#)
nmw_run, [23](#)
- Outline, [23](#)
- ParseOut, [24](#)
PrepPDF, [24](#)
PrinMTxt, [25](#)
PrinTxt, [25](#)
- RemoveNA, [26](#)
ResTest, [26](#)
run.test.nm, [27](#)
- SESuccess, [27](#)
SumOut, [28](#)
- TabStep, [28](#)
TrimOut, [29](#)