

Package ‘pkgverse’

July 23, 2025

Version 0.0.1

Title Build a Meta-Package Universe

Description Build your own universe of packages similar to the 'tidyverse' package <<https://tidyverse.org/>> with this meta-package creator. Create a package-verse, or meta package, by supplying a custom name for the collection of packages and the vector of desired package names to include—and optionally supply a destination directory, an indicator of whether to keep the created package directory, and/or a vector of verbs implement via the 'usethis' <<http://usethis.r-lib.org/>> package.

Encoding UTF-8

LazyData true

ByteCompile true

RoxygenNote 6.1.0.9000

Imports devtools, usethis, utils

License CC0

URL <https://pkgverse.mikewk.com>

BugReports <https://github.com/mkearney/pkgverse/issues>

NeedsCompilation no

Author Michael Wayne Kearney [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-0730-4694>>)

Maintainer Michael Wayne Kearney <kearneymw@missouri.edu>

Repository CRAN

Date/Publication 2018-11-14 09:10:06 UTC

Contents

pkgverse	2
Index	3

 pkgverse

pkgverse

Description

Create your own pkgverse

Usage

```
pkgverse(pkg, pkgs, keep = FALSE, use = NULL, install_if = FALSE)
```

Arguments

pkg	Name of your set of packages. It's recommended that users append this name with something like 'verse' or otherwise provide some kind of explicit/obvious indicator that the package name is a stand in for a selection of packages.
pkgs	Character vector of package names.
keep	If not 'FALSE', then used to indicate location to keep the 'pkg' dir (name), which should <u>not</u> include the 'pkg' name but should exist. It will be 'path.expand()'ed and tested for presence.
use	If not 'NULL' (the default), then a character vector of 'usethis' "use" functions (the bit after the first underscore) that make sense for a package.
install_if	Logical indicating whether to install (from CRAN) any packages in 'pkgs' that are not already installed on the system. Defaults to 'FALSE'.

Value

Installs a package of desired name, which, when loaded, will load, handle, and display conflicts of the packages supplied via pkgs.

Examples

```
## Not run:

## vector of pkgs
tidyweb <- c("curl", "jsonlite", "httr", "xml2", "rvest", "purrr", "dplyr",
  "stringi", "gdns", "urltools", "iptools", "seleniumPipes", "webdriver",
  "HARtools", "xslt", "V8", "webreadr", "openssl", "splashr")

## create tidyweb pkgverse
pkgverse("tidyweb", tidyweb,
  keep = "~/packages",
  use = c("readme_rmd", "rstudio", "testthat", "mit_license", "git")
)

## End(Not run)
```

Index

pkgverse, [2](#)