

Package ‘smd’

July 23, 2025

Type Package

Title Compute Standardized Mean Differences

Version 0.8.0

Description Computes standardized mean differences and confidence intervals for multiple data types based on Yang, D., & Dalton, J. E. (2012) <<https://support.sas.com/resources/papers/proceedings12/335-2012.pdf>>.

Imports MASS (>= 7.3-50), methods (>= 3.5.1)

Suggests testthat, stddiff, tableone, knitr, dplyr, purrr, markdown, rmarkdown

License MIT + file LICENSE

URL <https://bsaul.github.io/smd/>

BugReports <https://github.com/bsaul/smd/issues>

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

Repository CRAN

NeedsCompilation no

Author Bradley Saul [aut, cre],
Alex Breskin [ctb],
Catie Wiener [ctb],
Matt Phelan [ctb],
Daniel Sjoberg [ctb],
Nuvan Rathnayaka [ctb],
Malcolm Barrett [ctb]

Maintainer Bradley Saul <bradleysaul@fastmail.com>

Date/Publication 2025-02-12 17:50:02 UTC

Contents

smd	2
Index	4

smd

*Compute Standardized Mean Difference***Description**

Computes the standardized mean difference (SMD) between two groups.

$$d = \sqrt{D'S^{-1}D}$$

where D is a vector of differences between group 1 and 2 and S is the covariance matrix of these differences. If D is length 1, the result is multiplied by $sign(D)$.

In the case of a numeric or integer variable, this is equivalent to:

$$d = \frac{\bar{x}_1 - \bar{x}_2}{\sqrt{(s_1^2 + s_2^2)/2}}$$

where \bar{x}_g is the sample mean for group g and s_g^2 is the sample variance.

For a logical or factor with only two levels, the equation above is $\bar{x}_g = \hat{p}_g$, i.e. the sample proportion and $s_g^2 = \hat{p}_g(1 - \hat{p}_g)$.

When using the SMD to evaluate the effectiveness of weighting in achieving covariate balance, it is important to isolate the change in SMD before and after weighting to the change in mean difference, so the denominator (covariance matrix) must be held constant (Stuart 2008, doi:10.1002/sim.3207). By default, the unweighted covariance matrix is used to compute SMD in both the unweighted and weighted case. If the weights are not being used to adjust for covariate imbalance (e.g. case weights), the `unwgt.var` argument can be set to `FALSE` to use the weighted covariance matrix as the denominator.

Usage

```
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwgt.var = TRUE)

## S4 method for signature 'character,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwgt.var = TRUE)

## S4 method for signature 'character,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwgt.var = TRUE)

## S4 method for signature 'logical,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwgt.var = TRUE)

## S4 method for signature 'logical,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwgt.var = TRUE)

## S4 method for signature 'matrix,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwgt.var = TRUE)
```

```
## S4 method for signature 'matrix,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwtg.var = TRUE)

## S4 method for signature 'list,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwtg.var = TRUE)

## S4 method for signature 'list,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwtg.var = TRUE)

## S4 method for signature 'data.frame,ANY,missing'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwtg.var = TRUE)

## S4 method for signature 'data.frame,ANY,numeric'
smd(x, g, w, std.error = FALSE, na.rm = FALSE, gref = 1L, unwtg.var = TRUE)
```

Arguments

x	a vector or matrix of values
g	a vector of at least 2 groups to compare. This should be coercible to a factor.
w	a vector of numeric weights (optional)
std.error	Logical indicator for computing standard errors using <code>compute_smd_var</code> . Defaults to FALSE.
na.rm	Remove NA values from x? Defaults to FALSE.
gref	an integer indicating which level of g to use as the reference group. Defaults to 1.
unwtg.var	Use unweighted or weighted covariance matrix. Defaults to TRUE

Value

a data.frame containing standardized mean differences between levels of g for values of x. The data.frame contains the columns:

- term: the level being compared to the reference level
- estimate: SMD estimates
- std.error: (if std.error = TRUE) SMD standard error estimates

Examples

```
x <- rnorm(100)
g <- rep(1:2, each = 50)
smd(x, g)
```

Index

`compute_smd_var`, 3

`smd`, 2

`smd, character, ANY, missing-method (smd)`,
2

`smd, character, ANY, numeric-method (smd)`,
2

`smd, data.frame, ANY, missing-method
(smd)`, 2

`smd, data.frame, ANY, numeric-method
(smd)`, 2

`smd, list, ANY, missing-method (smd)`, 2

`smd, list, ANY, numeric-method (smd)`, 2

`smd, logical, ANY, missing-method (smd)`, 2

`smd, logical, ANY, numeric-method (smd)`, 2

`smd, matrix, ANY, missing-method (smd)`, 2

`smd, matrix, ANY, numeric-method (smd)`, 2