

Package ‘urlshorteneR’

July 22, 2025

Type Package

Title R Wrapper for the 'Bit.ly' and 'Is.gd'/'v.gd' URL Shortening Services

Description Allows using two URL shortening services, which also provide expanding and analytic functions. Specifically developed for 'Bit.ly' (which requires OAuth 2.0) and 'is.gd' (no API key).

Version 2.0.0

Date 2025-04-13

Maintainer John Malc <cincenko@outlook.com>

Encoding UTF-8

Depends R (>= 4.2)

Imports htr2 (>= 1.1.2), jsonlite (>= 2.0.0), stringr (>= 1.5.1),
lubridate (>= 1.9.4), assertthat (>= 0.2.1), shiny (>= 1.10.0),
clipr (>= 0.8.0), miniUI (>= 0.1.1.1), cli (>= 3.6.4)

Suggests roxygen2 (>= 7.3.2), knitr (>= 1.50), testthat (>= 3.2.3),
rmarkdown (>= 2.29), httpuv (>= 1.6.15), stringi (>= 1.8.7),
covr (>= 3.6.4), lintr (>= 3.2.0), dotenv (>= 1.0.3)

VignetteBuilder knitr

License Apache License 2.0

URL <https://github.com/dmpe/urlshorteneR>

BugReports <https://github.com/dmpe/urlshorteneR/issues>

RoxygenNote 7.3.2

NeedsCompilation no

Author John Malc [aut, cre] (@dmpe),
Andrea Dodet [ctb] (@andodet),
Stephen Synchronicity [ctb] (@yogat3ch)

Repository CRAN

Date/Publication 2025-04-13 16:00:02 UTC

Contents

bitly_add_cust_bitlink	3
bitly_app_details	4
bitly_bsds	4
bitly_bsds_overrides	5
bitly_create_bitlink	6
bitly_create_campaigns	7
bitly_create_channel	8
bitly_expand_link	9
bitly_qr_create_code	10
bitly_rate_limits	11
bitly_retrieve_bitlink	11
bitly_retrieve_bitlinks_by_groups	12
bitly_retrieve_campaign	13
bitly_retrieve_campaigns	14
bitly_retrieve_channel	15
bitly_retrieve_channels	16
bitly_retrieve_clicks	17
bitly_retrieve_clicks_summary	18
bitly_retrieve_cust_bitlink	19
bitly_retrieve_cust_bitlink_clicks_history	19
bitly_retrieve_cust_bitlink_metrics_destination	20
bitly_retrieve_destination_metrics	21
bitly_retrieve_group	22
bitly_retrieve_groups	22
bitly_retrieve_group_click_metrics_by_cities	23
bitly_retrieve_group_click_metrics_by_countries	24
bitly_retrieve_group_click_metrics_by_devices	25
bitly_retrieve_group_click_metrics_by_ref_networks	26
bitly_retrieve_group_feature_usage	27
bitly_retrieve_group_pref	27
bitly_retrieve_group_shorten_counts	28
bitly_retrieve_links_grouped	29
bitly_retrieve_metrics_by_countries	31
bitly_retrieve_metrics_by_referrers	32
bitly_retrieve_metrics_by_referrers_by_domain	33
bitly_retrieve_org	34
bitly_retrieve_orgs	34
bitly_retrieve_org_plan_limits	35
bitly_retrieve_org_shorten_counts	36
bitly_retrieve_org_shorten_counts_by_group	37
bitly_retrieve_sorted_bitlinks_by_groups	37
bitly_retrieve_sorted_links	38
bitly_retrieve_tags	40
bitly_shorten_link	40
bitly_update_bitlink	41
bitly_update_campaign	43

<i>bitly_add_cust_bitlink</i>	3
bitly_update_channel	44
bitly_update_cust_bitlink	45
bitly_update_group	46
bitly_update_group_pref	47
bitly_update_user	48
bitly_user_info	49
bitly_user_metrics_referring_domains	50
isgd_LinksExpand	51
isgd_LinksShorten	52
is_bitly_user_premium_holder	53
shortenerAddin	53
vgd_LinksExpand	53
vgd_LinksShorten	54
Index	56

bitly_add_cust_bitlink
Add Custom Bitlink (Premium)

Description

Add a Keyword to a Bitlink

Usage

```
bitly_add_cust_bitlink(
    bitlink_id = NULL,
    custom_bitlink = NULL,
    showRequestURL = FALSE
)
```

Arguments

- bitlink_id - string
- custom_bitlink - A Custom Bitlink made of the domain and keyword
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Custom Bitlinks

Custom Bitlinks have both a branded short domain (BSD) AND a customized backend. For example, bit.ly/bitlinks would not be considered a Custom Bitlink because it does not have a branded short domain. es.pn/2yxklu would not be considered a custom Bitlink because while it has a branded short domain, it doesn't have a customized backhalf. An example of a link that would live in this section is es.pn/SuperBowl

See Also

<https://dev.bitly.com/api-reference/#addCustomBitlink>

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_add_cust_bitlink(custom_bitlink = "es.pn/SuperBowl", bitlink_id = "")

## End(Not run)
```

bitly_app_details *Retrieve OAuth App*

Description

Retrieve details for the provided OAuth App client ID

Usage

```
bitly_app_details(
  client_id = "be03aead58f23bc1aee6e1d7b7a1d99d62f0ede8",
  showRequestURL = F
)
```

Arguments

client_id - The client ID of an OAuth app
 showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

bitly_bsds *Fetch all Branded Short Domains*

Description

BSDs is an acronym for branded short domains. This is a custom 15 character or less domain for bitlinks. This allows you to customize the domain to your brand.

Usage

```
bitly_bsds(showRequestURL = F)
```

Arguments

showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#getBSDs>

bitly_bsds_overrides *Branded Short Domains Group Overrides (Premium)*

Description

Retrieves all account overrides matching specified group_guid and bsd query filters.

Usage

```
bitly_bsds_overrides(group_id = NA, showRequestURL = F)
```

Arguments

group_id - a required string | A GUID for a Bitly group

showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#getOverridesForGroups>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
ui <- bitly_user_info(showRequestURL = TRUE)  
bsds_over <- bitly_bsds_overrides(group_id = ui$default_group_guid[1])  
  
## End(Not run)
```

bitly_create_bitlink *Create a short Bitlink*

Description

See <https://dev.bitly.com/docs/getting-started/rate-limits> and <https://dev.bitly.com/api-reference/#createFullBitlink> Convert a long url to a Bitlink and set additional parameters.

Usage

```
bitly_create_bitlink(
    long_url = NULL,
    domain = "bit.ly",
    title = NULL,
    tags = NULL,
    group_guid = NULL,
    deeplinks_list = list(app_uri_path = NULL, install_type = NULL, install_url = NULL,
        app_id = NULL),
    showRequestURL = FALSE
)
```

Arguments

long_url	- required, a long URL to be shortened (example: https://www.idnes.cz). Must contain http/https
domain	- (optional) the short domain to use; either bit.ly, j.mp, or bitly.com or a custom short domain. The default for this parameter is the short domain selected by each user in their bitly account settings. Passing a specific domain via this parameter will override the default settings.
title	- title of the bitlink
tags	- Array of string, use e.g. c("test1", "test2")
group_guid	- a GUID for a Bitly group
deeplinks_list	- a list containing parameters below
showRequestURL	- show URL which has been build and requested from server. For debug purposes.
app_uri_path	- app_uri_path
install_type	- install_type
install_url	- install_url
app_id	- app_id

Value

id - a short bitly identifier for long_url which is unique to the given account.

long_url - This may not always be equal to the URL requested, as some URL normalization may occur (e.g., due to encoding differences, or case differences in the domain). This long_url will always be functionally identical the the request parameter.

link - an bitly id with http(s) prefix

Note

Look in the vignette for bulk shortening of URLs. Each call of this function == 1 API call. Take that into consideration due to limits etc.

The bitly API does not support shortening more than one long URL with a single API call. Meaning 1 Long URL = 1 Function call.

Long URLs should be URL-encoded. You can not include a longUrl in the request that has &, ?, #, or other reserved parameters without first encoding it.

The default value for the domain parameter is selected by each user from within their bitly account settings at <<https://app.bitly.com/settings/api/>>.

Long URLs should not contain spaces: any longUrl with spaces will be rejected. All spaces should be either percent encoded spaces are all indications of errors. Please remember to strip leading and trailing whitespace from any user input before shortening.

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_create_bitlink(long_url = "http://slovník.seznam.cz/")

## End(Not run)
```

bitly_create_campaigns

Create Campaign (Premium)

Description

Create a new campaign

Usage

```
bitly_create_campaigns(
  group_guid = NULL,
  channel_guids = NULL,
  description = NULL,
  name = NULL,
  showRequestURL = T
)
```

Arguments

group_guid - a GUID for a Bitly group
channel_guids - a list of strings
description - description of campaign
name - its name
showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Campaigns

Bit.ly Campaigns allows you to build and manage omnichannel campaigns.

See Also

<https://dev.bitly.com/api-reference/#createCampaign>

Examples

```
## Not run:  
cc <- bitly_create_campaigns(  
  group_guid = "testing", showRequestURL = TRUE, channel_guids = list("1", "2", "3"),  
  description = "description", name = "name"  
)  
  
## End(Not run)
```

bitly_create_channel *Create channel (Premium)*

Description

Create a new channel

Usage

```
bitly_create_channel(  
  group_guid = NULL,  
  guid = NULL,  
  name = NULL,  
  modified = NULL,  
  created = NULL,  
  campaign_guid = NULL,  
  bitlink_id = NULL,  
  showRequestURL = T  
)
```


Arguments

group_guid - a GUID for a Bitly group
guid - ID for a channel
name - its name
modified - string | ISO_TIMESTAMP
created - string | ISO_TIMESTAMP
campaign_guid - string | A GUID for a Bitly campaign
bitlink_id - string
showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Campaigns

Bit.ly Campaigns allows you to build and manage omnichannel campaigns.

See Also

<https://dev.bitly.com/api-reference/#createChannel>

Examples

```
## Not run:  
gc <- bitly_create_channel(group_guid = "testing", ...)  
  
## End(Not run)
```

bitly_expand_link *Expand a Bitlink*

Description

See <https://dev.bitly.com/api-reference/#expandBitlink> This endpoint returns public information for a Bitlink.

Usage

```
bitly_expand_link(  
  bitlink_id = NULL,  
  access_token = NULL,  
  showRequestURL = FALSE  
)
```

Arguments

bitlink_id - string
 access_token - bearer token which might be also provided directly
 showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Value

long_url - a full URL to which bitlink points to

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_expand_link(bitlink_id = "bit.ly/DPetrov")
bitly_expand_link(bitlink_id = "on.natgeo.com/1bEVhwE")

## manyHashes <- list("bit.ly/DPetrov", "bit.ly/1QU8CFm", "bit.ly/1R1LPSE", "bit.ly/1LNqqva")
## for (u in 1:length(manyHashes)) {
##   print(bitly_expand_link(bitlink_id = manyHashes[[u]], showRequestURL = TRUE))
## }

## End(Not run)
```

bitly_qr_create_code *Create QR code with bit.ly link*

Description

Create a new QR Code and return its metadata

Usage

```
bitly_qr_create_code(title = NULL, group_guid = NULL, bitly_link = NULL)
```

Arguments

title - a required string
 group_guid - group id
 bitly_link - a bit.ly link

See Also

<https://dev.bitly.com/api-reference/#createQRCodePublic>

Examples

```
## Not run:
bitly_bearerToken("access token")
qr <- bitly_qr_create_code(group_guid = "Be2oejZbDDc", bitly_link = "bit.ly/abc1234")

## End(Not run)
```

```
bitly_rate_limits      bitly_rate_limits
```

Description

Provides bit.ly rate limits by endpoint. See <https://dev.bitly.com/api-reference/#getPlatformLimitss>

Usage

```
bitly_rate_limits(showRequestURL = F)
```

Arguments

showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Value

data.frame of end points and their rate limits by action

```
bitly_retrieve_bitlink
      Retrieve a Bitlink
```

Description

This endpoint returns information for a Bitlink.

Usage

```
bitly_retrieve_bitlink(bitlink = NULL, showRequestURL = FALSE)
```

Arguments

bitlink - required, a Bitlink made of the domain and hash
showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

See <https://dev.bitly.com/api-reference/#getBitlink>

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_retrieve_bitlink(bitlink = "cnn.it/2HomWGB")

## End(Not run)
```

bitly_retrieve_bitlinks_by_groups
Retrieve Bitlinks by Group

Description

See <https://dev.bitly.com/api-reference/#getBitlinksByGroup> Retrieve a paginated collection of Bitlinks for a Group

Usage

```
bitly_retrieve_bitlinks_by_groups(  
  group_guid = NULL,  
  size = 50,  
  page = 1,  
  showRequestURL = FALSE,  
  keyword = NULL,  
  query_q = NULL,  
  created_before = NULL,  
  created_after = NULL,  
  modified_after = NULL,  
  archived = "both",  
  deeplinks = "both",  
  campaign_guid = NULL,  
  channel_guid = NULL,  
  custom_bitlink = "both",  
  tags = NULL,  
  encoding_login = NULL,  
  domain_deeplinks = "both"  
)
```

Arguments

group_guid - a GUID for a Bitly group
size - The quantity of items to be returned

page	- Default: 1 Integer specifying the numbered result at which to start
showRequestURL	- show URL which has been build and requested from server. For debug purposes.
keyword	- Custom keyword to filter on history entries
query_q	- a query to look for in bitlinks; acts a filter
created_before	- Timestamp as an integer unix epoch
created_after	- Timestamp as an integer unix epoch
modified_after	- Timestamp as an integer unix epoch, see as_datetime or anytime's as_datetime
archived	- string Default: "off" Enum:"on" "off" "both" Whether or not to include archived bitlinks
deeplinks	- string Default: "both" Enum:"on" "off" "both" Filter to only Bitlinks that contain deeplinks
campaign_guid	- string A GUID for a Bitly campaign
channel_guid	- Filter to return only links for the given channel GUID, can be provided, overrides all other parameters
custom_bitlink	- string Default: "both" Enum:"on" "off" "both"
tags	- Array of string, use e.g. c("test1", "test2")
encoding_login	- Array of string Filter by the login of the authenticated user that created the Bitlink
domain_deeplinks	- string Default: "both" Enum:"on" "off" "both" Filter to only Bitlinks that contain deeplinks configured with a custom domain

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_retrieve_bitlinks_by_groups(group_guid = "bit.ly/DPetrov", keyword = "novy titulek")

## End(Not run)
```

```
bitly_retrieve_campaign
```

Retrieve a Campaign

Description

Retrive details for a campaign

Usage

```
bitly_retrieve_campaign(campaign_guid = NULL, showRequestURL = T)
```

Arguments

- campaign_guid - string | A GUID for a Bitly campaign
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Campaigns

Bit.ly Campaigns allows you to build and manage omnichannel campaigns.

See Also

<https://dev.bitly.com/api-reference/#getCampaign>

Examples

```
## Not run:  
gc <- bitly_retrieve_campaign(campaign_guid = "testing")  
  
## End(Not run)
```

bitly_retrieve_campaigns
Retrieve campaigns (Premium)

Description

Retrieve the campaigns for the current user

Usage

```
bitly_retrieve_campaigns(group_guid = NULL, showRequestURL = T)
```

Arguments

- group_guid - a GUID for a Bitly group
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Campaigns

Bit.ly Campaigns allows you to build and manage omnichannel campaigns.

See Also

<https://dev.bitly.com/api-reference/#getCampaigns>

Examples

```
## Not run:  
gc <- bitly_retrieve_campaigns(group_guid = "testing")  
  
## End(Not run)
```

bitly_retrieve_channel
Get a Channel (Premium)

Description

Get a channel's details

Usage

```
bitly_retrieve_channel(channel_guid = NULL, showRequestURL = T)
```

Arguments

channel_guid - GUID of a target channel
showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Campaigns

Bit.ly Campaigns allows you to build and manage omnichannel campaigns.

See Also

<https://dev.bitly.com/api-reference/#getChannel>

Examples

```
## Not run:  
gc <- bitly_retrieve_channel(channel_guid = "testing")  
  
## End(Not run)
```

bitly_retrieve_channels
Retrieve channels (Premium)

Description

Retrieve the channels available to a user

Usage

```
bitly_retrieve_channels(  
  group_guid = NULL,  
  campaign_guid = NULL,  
  showRequestURL = T  
)
```

Arguments

group_guid - a GUID for a Bitly group

campaign_guid - string | A GUID for a Bitly campaign

showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Campaigns

Bit.ly Campaigns allows you to build and manage omnichannel campaigns.

See Also

<https://dev.bitly.com/api-reference/#getChannels>

Examples

```
## Not run:  
gc <- bitly_retrieve_channels(group_guid = "testing", campaign_guid = "test")  
  
## End(Not run)
```

bitly_retrieve_clicks *Get Clicks for a Bitlink*

Description

See <https://dev.bitly.com/api-reference/#getClicksForBitlink> This will return the click counts for a specified Bitlink. This returns an array with clicks based on a date.

Usage

```
bitly_retrieve_clicks(  
  bitlink = NULL,  
  size = 50,  
  unit_reference = NULL,  
  unit = NULL,  
  units = -1,  
  showRequestURL = FALSE  
)
```

Arguments

<code>bitlink</code>	- required, a Bitlink made of the domain and hash
<code>size</code>	- The quantity of items to be returned
<code>unit_reference</code>	- string An ISO-8601 timestamp, indicating the most recent time for which to pull metrics. Will default to current time.
<code>unit</code>	- A unit of time
<code>units</code>	- An integer representing the time units to query data for. pass -1 to return all units of time.
<code>showRequestURL</code>	- show URL which has been build and requested from server. For debug purposes.

Examples

```
## Not run:  
bitly_bearerToken("access token")  
bitly_retrieve_clicks(bitlink = "cnn.it/2HomWGB", unit = "day", units = -1, size = 100)  
  
## End(Not run)
```

`bitly_retrieve_clicks_summary`*Get Clicks Summary for a Bitlink*

Description

See <https://dev.bitly.com/api-reference/#getClicksSummaryForBitlink> This will return the click counts for a specified Bitlink. This rolls up all the data into a single field of clicks.

Usage

```
bitly_retrieve_clicks_summary(  
  bitlink = NULL,  
  size = 50,  
  unit_reference = NULL,  
  unit = NULL,  
  units = -1,  
  showRequestURL = FALSE  
)
```

Arguments

<code>bitlink</code>	- required, a Bitlink made of the domain and hash
<code>size</code>	- The quantity of items to be returned
<code>unit_reference</code>	- string An ISO-8601 timestamp, indicating the most recent time for which to pull metrics. Will default to current time.
<code>unit</code>	- A unit of time
<code>units</code>	- An integer representing the time units to query data for. pass -1 to return all units of time.
<code>showRequestURL</code>	- show URL which has been build and requested from server. For debug purposes.

Examples

```
## Not run:  
bitly_bearerToken("access token")  
bitly_retrieve_clicks_summary(bitlink = "cnn.it/2HomWGB", unit = "day", units = -1, size = 100)  
  
## End(Not run)
```

bitly_retrieve_cust_bitlink
Retrieve Custom Bitlink (Premium)

Description

Retrieve the details and history of a Custom Bitlink

Usage

```
bitly_retrieve_cust_bitlink(custom_bitlink = NULL, showRequestURL = FALSE)
```

Arguments

`custom_bitlink` - A Custom Bitlink made of the domain and keyword
`showRequestURL` - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#getCustomBitlink>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
bitly_retrieve_cust_bitlink(custom_bitlink = "es.pn/SuperBowl")  
  
## End(Not run)
```

bitly_retrieve_cust_bitlink_clicks_history
Get Clicks for a Custom Bitlink's Entire History (Premium)

Description

Returns the click counts for the specified link. This returns an array with clicks based on a date.

Usage

```
bitly_retrieve_cust_bitlink_clicks_history(  
  custom_bitlink = NULL,  
  showRequestURL = FALSE  
)
```

Arguments

- custom_bitlink - A Custom Bitlink made of the domain and keyword
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#getClicksForCustomBitlink>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
bitly_retrieve_cust_bitlink_clicks_history(custom_bitlink = "es.pn/SuperBowl")  
  
## End(Not run)
```

bitly_retrieve_cust_bitlink_metrics_destination

Get Metrics for a Custom Bitlink by Destination (Premium)

Description

Returns click metrics for the specified link by its historical destinations.

Usage

```
bitly_retrieve_cust_bitlink_metrics_destination(  
  custom_bitlink = NULL,  
  showRequestURL = FALSE  
)
```

Arguments

- custom_bitlink - A Custom Bitlink made of the domain and keyword
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#getCustomBitlinkMetricsByDestination>

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_retrieve_cust_bitlink_metrics_destination(custom_bitlink = "es.pn/SuperBowl")

## End(Not run)
```

bitly_retrieve_destination_metrics

Get Metrics for a Custom Bitlink by destination (Premium)

Description

Get Click Metrics for a Custom Bitlink by historical Bitlink destinations

Usage

```
bitly_retrieve_destination_metrics(
  custom_bitlink = NULL,
  showRequestURL = FALSE
)
```

Arguments

custom_bitlink - A Custom Bitlink made of the domain and keyword

showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#getCustomBitlinkMetricsByDestination>

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_retrieve_destination_metrics(custom_bitlink = "es.pn/SuperBowl")

## End(Not run)
```

bitly_retrieve_group *Retrieve a single group*

Description

Retrive details for a specific group that a user belongs to.

Usage

```
bitly_retrieve_group(group_id = NA, showRequestURL = F)
```

Arguments

group_id - a required string | A GUID for a Bitly group
showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#getGroup>

Examples

```
## Not run:  
ui <- bitly_user_info(showRequestURL = TRUE)  
rg <- bitly_retrieve_group(group_guid = ui$default_group_guid)  
  
## End(Not run)
```

bitly_retrieve_groups *Retrieve a list of all groups*

Description

Retrive details for all groups that a user belongs to.

Usage

```
bitly_retrieve_groups(organization_id = NULL, showRequestURL = F)
```

Arguments

- organization_id - an optional string parameter | A GUID for a Bitly organization
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#getGroups>

Examples

```
## Not run:  
rg <- bitly_retrieve_groups("") # will still work ok  
  
## End(Not run)
```

bitly_retrieve_group_click_metrics_by_cities

Get Click Metrics for a specified group by city (Premium)

Description

Returns the geographic origins of click traffic by city for the specified group. Requires a premium account.

Usage

```
bitly_retrieve_group_click_metrics_by_cities(group_id = NA, showRequestURL = F)
```

Arguments

- group_id - a required string | A GUID for a Bitly group
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference/#getGroupMetricsByCities>

Examples

```
## Not run:
ui <- bitly_user_info(showRequestURL = TRUE)
rg <- bitly_retrieve_group_click_metrics_by_cities(group_id = ui$default_group_guid[1])

## End(Not run)
```

```
bitly_retrieve_group_click_metrics_by_countries
Get Click Metrics for a Group by countries
```

Description

This endpoint will return metrics about the countries referring click traffic rolled up to a Group

Usage

```
bitly_retrieve_group_click_metrics_by_countries(
  group_id = NA,
  showRequestURL = F
)
```

Arguments

`group_id` - a required string | A GUID for a Bitly group
`showRequestURL` - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#getGroupMetricsByCountries>

Examples

```
## Not run:
ui <- bitly_user_info(showRequestURL = TRUE)
rg <- bitly_retrieve_group_click_metrics_by_countries(group_id = ui$default_group_guid[1])

## End(Not run)
```

`bitly_retrieve_group_click_metrics_by_devices`*Get Click Metrics for a specified group by devices (Premium)*

Description

Returns the device types generating click traffic to the specified group's links. Requires a premium account.

Usage

```
bitly_retrieve_group_click_metrics_by_devices(  
  group_id = NA,  
  showRequestURL = F  
)
```

Arguments

`group_id` - a required string | A GUID for a Bitly group

`showRequestURL` - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference/#getGroupMetricsByDevices>

Examples

```
## Not run:  
ui <- bitly_user_info(showRequestURL = TRUE)  
rg <- bitly_retrieve_group_click_metrics_by_devices(group_id = ui$default_group_guid[1])  
  
## End(Not run)
```

bitly_retrieve_group_click_metrics_by_ref_networks
Get Click Metrics for a Group by referring networks

Description

This endpoint will return metrics about the referring network click traffic rolled up to a Group

Usage

```
bitly_retrieve_group_click_metrics_by_ref_networks(  
  group_id = NA,  
  showRequestURL = F  
)
```

Arguments

`group_id` - a required string | A GUID for a Bitly group

`showRequestURL` - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#GetGroupMetricsByReferringNetworks>

Examples

```
## Not run:  
ui <- bitly_user_info(showRequestURL = TRUE)  
rg <- bitly_retrieve_group_click_metrics_by_ref_networks(group_id = ui$default_group_guid[1])  
  
## End(Not run)
```

`bitly_retrieve_group_feature_usage`*Retrieve group's feature limit usage*

Description

Get a group's current feature limit usage.

Usage

```
bitly_retrieve_group_feature_usage(group_id = NA, showRequestURL = F)
```

Arguments

`group_id` - a required string | A GUID for a Bitly group
`showRequestURL` - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#getGroupFeatureUsage>

Examples

```
## Not run:  
ui <- bitly_user_info(showRequestURL = TRUE)  
rg <- bitly_retrieve_group_feature_usage(group_guid = ui$default_group_guid)  
  
## End(Not run)
```

`bitly_retrieve_group_pref`*Retrieve Group Preferences*

Description

Retrieve preferences for a specific group

Usage

```
bitly_retrieve_group_pref(group_id = NA, showRequestURL = F)
```

Arguments

- group_id - the group id the user belongs to
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#getGroupPreferences>

Examples

```
## Not run:
ui <- bitly_user_info(showRequestURL = TRUE)
group_pref <- bitly_retrieve_group_pref(group_id = ui$default_group_guid[1])

## End(Not run)
```

bitly_retrieve_group_shorten_counts
Retrieve Group Shorten Counts

Description

Get all the shorten counts for a specific group

Usage

```
bitly_retrieve_group_shorten_counts(group_id = NA, showRequestURL = F)
```

Arguments

- group_id - a required string | A GUID for a Bitly group
- showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#getGroupShortenCounts>

Examples

```
## Not run:
ui <- bitly_user_info(showRequestURL = TRUE)
rg <- bitly_retrieve_group_shorten_counts(group_id = ui$default_group_guid[1])

## End(Not run)
```

bitly_retrieve_links_grouped
Retrieve Bitlinks by Group

Description

Retrieve a paginated collection of Bitlinks for a Group

Usage

```
bitly_retrieve_links_grouped(  
  group_id = NA,  
  keyword = NULL,  
  search_query = NULL,  
  created_before = NULL,  
  created_after = NULL,  
  modified_after = NULL,  
  archived = "off",  
  deeplinks = "both",  
  domain_deeplinks = "both",  
  campaign_guid = NULL,  
  channel_guid = NULL,  
  custom_bitlink = "both",  
  tags = NULL,  
  encoding_login = NULL,  
  page = 1,  
  size = 50,  
  showRequestURL = F  
)
```

Arguments

group_id - a required string | A GUID for a Bitly group
keyword - Custom keyword to filter on history entries
search_query - string | the value that you would like to search

created_before - Timestamp as an integer unix epoch
 created_after - Timestamp as an integer unix epoch
 modified_after - Timestamp as an integer unix epoch, see [as_datetime](#) or anytime's `as_datetime`
 archived - string | Default: "off" | Enum:"on" "off" "both" | Whether or not to include archived bitlinks
 deeplinks - string | Default: "both" | Enum:"on" "off" "both" | Filter to only Bitlinks that contain deeplinks
 domain_deeplinks - string | Default: "both" | Enum:"on" "off" "both" | Filter to only Bitlinks that contain deeplinks configured with a custom domain
 campaign_guid - Filter to return only links for the given campaign GUID, can be provided
 channel_guid - Filter to return only links for the given channel GUID, can be provided, overrides all other parameters
 custom_bitlink - string | Default: "both" | Enum:"on" "off" "both"
 tags - Array of string | filter by given tags
 encoding_login - Array of string | Filter by the login of the authenticated user that created the Bitlink
 page - Default: 1 | Integer specifying the numbered result at which to start
 size - string | Default: 50 | The quantity of items to be returned
 showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#getBitlinksByGroup>

Examples

```

## Not run:
ui <- bitly_user_info(showRequestURL = TRUE)
rg <- bitly_retrieve_links_grouped(group_id = ui$default_group_guid[1])

## End(Not run)

```

bitly_retrieve_metrics_by_countries
Get Metrics for a Bitlink by countries

Description

This endpoint will return metrics about the countries referring click traffic to a single Bitlink.

Usage

```
bitly_retrieve_metrics_by_countries(  
  bitlink = NULL,  
  size = 100,  
  unit = NULL,  
  unit_reference = NULL,  
  units = -1,  
  showRequestURL = FALSE  
)
```

Arguments

bitlink	- required, a Bitlink made of the domain and hash
size	- The quantity of items to be returned
unit	- A unit of time
unit_reference	- string An ISO-8601 timestamp, indicating the most recent time for which to pull metrics. Will default to current time.
units	- An integer representing the time units to query data for. pass -1 to return all units of time.
showRequestURL	- show URL which has been build and requested from server. For debug purposes.

See Also

<https://dev.bitly.com/api-reference/#getMetricsForBitlinkByCountries>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
bitly_retrieve_metrics_by_countries(  
  bitlink = "bit.ly/DPetrov", unit = "day", units = -1,  
  size = 100  
)  
  
## End(Not run)
```

`bitly_retrieve_metrics_by_referrers`*Get Metrics for a Bitlink by referrers*

Description

This endpoint will return metrics about the referrers referring click traffic to a single Bitlink.

Usage

```
bitly_retrieve_metrics_by_referrers(  
  bitlink = NULL,  
  size = 100,  
  unit = NULL,  
  unit_reference = NULL,  
  units = -1,  
  showRequestURL = FALSE  
)
```

Arguments

<code>bitlink</code>	- required, a Bitlink made of the domain and hash
<code>size</code>	- The quantity of items to be returned
<code>unit</code>	- A unit of time
<code>unit_reference</code>	- string An ISO-8601 timestamp, indicating the most recent time for which to pull metrics. Will default to current time.
<code>units</code>	- An integer representing the time units to query data for. pass -1 to return all units of time.
<code>showRequestURL</code>	- show URL which has been build and requested from server. For debug purposes.

See Also

<https://dev.bitly.com/api-reference/#getMetricsForBitlinkByReferrers>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
bitly_retrieve_metrics_by_referrers(  
  bitlink = "bit.ly/DPetrov", unit = "day",  
  units = -1, size = 100  
)  
  
## End(Not run)
```

bitly_retrieve_metrics_by_referrers_by_domain
Get Metrics for a Bitlink by referrers by domain

Description

This endpoint will group referrers metrics about a single Bitlink.

Usage

```
bitly_retrieve_metrics_by_referrers_by_domain(  
  bitlink = NULL,  
  size = 50,  
  unit_reference = NULL,  
  unit = NULL,  
  units = -1,  
  showRequestURL = FALSE  
)
```

Arguments

bitlink	- required, a Bitlink made of the domain and hash
size	- string Default: 50 The quantity of items to be returned
unit_reference	- string An ISO-8601 timestamp, indicating the most recent time for which to pull metrics. Will default to current time.
unit	- string Default: "day", Enum: "minute" "hour" "day" "week" "month" A unit of time
units	- integer Default: -1 An integer representing the time units to query data for. pass -1 to return all units of time.
showRequestURL	- an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#getMetricsForBitlinkByReferrersByDomains>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
bitly_retrieve_metrics_by_referrers_by_domain(  
  bitlink = "bit.ly/DPetrov", unit = "day",  
  units = -1, size = 100  
)  
  
## End(Not run)
```

bitly_retrieve_org *Retrieve a single Organization*

Description

Retrive details for the specified organization.

Usage

```
bitly_retrieve_org(organization_id = NULL)
```

Arguments

organization_id
- a required string | A GUID for a Bitly organization. You may also simply pass "" (double quotes), but this should be avoided at all costs.

Organizations

Organizations are part of our hierarchy. This is the top level where a group and user will belong.

See Also

<https://dev.bitly.com/api-reference/#getOrganization>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
all_orgs <- bitly_retrieve_orgs()  
ro <- bitly_retrieve_org(organization_id = all_orgs$guid)  
  
## End(Not run)
```

bitly_retrieve_orgs *Retrieve all Organizations*

Description

Retrieve a list of organizations

Usage

```
bitly_retrieve_orgs()
```

Organizations

Organizations are part of our hierarchy. This is the top level where a group and user will belong.

See Also

<https://dev.bitly.com/api-reference/#getOrganizations>

Examples

```
## Not run:
bitly_bearerToken("access token")
ros <- bitly_retrieve_orgs()

## End(Not run)
```

```
bitly_retrieve_org_plan_limits
Get Plan Limits
```

Description

Returns all plan limits and counts available for an organization.

Usage

```
bitly_retrieve_org_plan_limits(organization_id = NULL)
```

Arguments

```
organization_id
- a required string | A GUID for a Bitly organization. You may also simply pass "" (double quotes), but this should be avoided at all costs.
```

Organizations

Organizations are part of our hierarchy. This is the top level where a group and user will belong.

See Also

<https://dev.bitly.com/api-reference/#getPlanLimits>

Examples

```
## Not run:
bitly_bearerToken("access token")
all_orgs <- bitly_retrieve_orgs()
plan <- bitly_retrieve_org_plan_limits(organization_id = all_orgs$guid)

## End(Not run)
```

`bitly_retrieve_org_shorten_counts`*Retrieve Organization Shorten Counts*

Description

Retrieve all the shorten counts for a specific organization

Usage

```
bitly_retrieve_org_shorten_counts(organization_id = NULL)
```

Arguments

`organization_id`

- a required string | A GUID for a Bitly organization. You may also simply pass "" (double quotes), but this should be avoided at all costs.

Value

facet - Enum: "countries" "referrers" "referrers_by_domain" "referring_domains" "referring_networks" "shorten_counts"

Organizations

Organizations are part of our hierarchy. This is the top level where a group and user will belong.

See Also

<https://dev.bitly.com/api-reference/#getOrganizationShortenCounts>

Examples

```
## Not run:
bitly_bearerToken("access token")
all_orgs <- bitly_retrieve_orgs()
osc <- bitly_org_shorten_counts(organization_id = all_orgs$guid)
df_org_short_counts <- data.frame(osc)

## End(Not run)
```

bitly_retrieve_org_shorten_counts_by_group
Retrieve Organization Shorten Counts by Group

Description

Returns the shorten counts for a specific organization by group for the current month.

Usage

```
bitly_retrieve_org_shorten_counts_by_group(organization_id = NULL)
```

Arguments

organization_id
- a required string | A GUID for a Bitly organization. You may also simply pass "" (double quotes), but this should be avoided at all costs.

Organizations

Organizations are part of our hierarchy. This is the top level where a group and user will belong.

See Also

<https://dev.bitly.com/api-reference/#getOrganizationShortenCountsByGroup>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
all_orgs <- bitly_retrieve_orgs()  
osc <- bitly_retrieve_org_shorten_counts_by_group(organization_id = all_orgs$guid)  
df_org_short_counts <- data.frame(osc)  
  
## End(Not run)
```

bitly_retrieve_sorted_bitlinks_by_groups
Retrieve Sorted Bitlinks for Group

Description

See <https://dev.bitly.com/api-reference/#getSortedBitlinks> This will retrieve a paginated response for Bitlinks that are sorted for the Group

Usage

```
bitly_retrieve_sorted_bitlinks_by_groups(  
  group_guid = NULL,  
  unit = "day",  
  units = -1,  
  sort = "clicks",  
  size = 50,  
  unit_reference = NULL,  
  showRequestURL = FALSE  
)
```

Arguments

`group_guid` - a GUID for a Bitly group

`unit` - A unit of time

`units` - An integer representing the time units to query data for. pass -1 to return all units of time.

`sort` - required, Enum:"clicks" - The type of sorting that you would like to do

`size` - The quantity of items to be returned

`unit_reference` - string | An ISO-8601 timestamp, indicating the most recent time for which to pull metrics. Will default to current time.

`showRequestURL` - show URL which has been build and requested from server. For debug purposes.

Examples

```
## Not run:  
bitly_bearerToken("access token")  
bitly_retrieve_sorted_bitlinks_by_groups(group_guid = "", sort = "clicks")  
  
## End(Not run)
```

bitly_retrieve_sorted_links

Retrieve Sorted Bitlinks for Group

Description

This will retrieve a paginated response for Bitlinks that are sorted for the Group. This method returns a combined object which end-user (you) have to further process for your needs.

Usage

```
bitly_retrieve_sorted_links(
  group_id = NA,
  to_sort_by = "clicks",
  unit = "day",
  units = -1,
  unit_reference = NULL,
  size = 50,
  showRequestURL = F
)
```

Arguments

group_id	- a required string A GUID for a Bitly group
to_sort_by	- a required string Enum: "clicks" The type of sorting that you would like to do
unit	- string Default: "day", Enum: "minute" "hour" "day" "week" "month" A unit of time
units	- integer Default: -1 An integer representing the time units to query data for. pass -1 to return all units of time.
unit_reference	- string An ISO-8601 timestamp, indicating the most recent time for which to pull metrics. Will default to current time.
size	- string Default: 50 The quantity of items to be returned
showRequestURL	- an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#getSortedBitlinks>

Examples

```
## Not run:
ui <- bitly_user_info(showRequestURL = TRUE)
rg <- bitly_retrieve_sorted_links(group_id = ui$default_group_guid[1])

## End(Not run)
```

bitly_retrieve_tags *Retrieve Tags by Group*

Description

Retrieve the currently used tags for a group

Usage

```
bitly_retrieve_tags(group_id = NA, showRequestURL = F)
```

Arguments

group_id - a required string | A GUID for a Bitly group
showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#getGroupTags>

Examples

```
## Not run:  
ui <- bitly_user_info(showRequestURL = TRUE)  
rg <- bitly_retrieve_tags(group_id = ui$default_group_guid[1])  
  
## End(Not run)
```

bitly_shorten_link *Shorten a Link*

Description

See <https://dev.bitly.com/api-reference/#createBitlink> Convert a long url to a Bitlink

Usage

```
bitly_shorten_link(
  domain = "bit.ly",
  group_guid = NULL,
  long_url = NULL,
  access_token = NULL,
  showRequestURL = FALSE
)
```

Arguments

domain	- (optional) the short domain to use; either bit.ly, j.mp, or bitly.com or a custom short domain. The default for this parameter is the short domain selected by each user in their bitly account settings. Passing a specific domain via this parameter will override the default settings.
group_guid	- a GUID for a Bitly group
long_url	- required, a long URL to be shortened (example: https://www.idnes.cz). Must contain http/https
access_token	- bearer token which might be also provided directly
showRequestURL	- show URL which has been build and requested from server. For debug purposes.

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_shorten_link(url = "http://www.seznam.cz/")
bitly_shorten_link(url = "http://www.seznam.cz/", showRequestURL = TRUE)

manyUrls <- list(
  "http://www.seznam.cz/", "http://www.seznamdas.cz/",
  "http://www.seznam.cz/asadasd", "http://www.seznam.cz/adqwrewtregt"
)
for (u in 1:length(manyUrls)) {
  print(bitly_shorten_link(long_url = manyUrls[[u]], showRequestURL = TRUE))
}

## End(Not run)
```

bitly_update_bitlink *Update a Bitlink*

Description

See <https://dev.bitly.com/api-reference/#updateBitlink> Update fields in the Bitlink

Usage

```
bitly_update_bitlink(
  bitlink = NULL,
  archived = NULL,
  tags = NULL,
  showRequestURL = FALSE,
  created_at = NULL,
  title = NULL,
  created_by = NULL,
  long_url = NULL,
  client_id = NULL,
  custom_bitlinks = NULL,
  link = NULL,
  id = NULL,
  deeplinks = list(bitlink = NULL, install_url = NULL, created = NULL, modified = NULL,
  app_uri_path = NULL, install_type = NULL, app_guid = NULL, guid = NULL, os = NULL)
)
```

Arguments

bitlink	- required, a Bitlink made of the domain and hash
archived	- string Default: "off" Enum:"on" "off" "both" Whether or not to include archived bitlinks
tags	- Array of string, use e.g. c("test1", "test2")
showRequestURL	- show URL which has been build and requested from server. For debug purposes.
created_at	- update created at parameter
title	- title of the bitlink
created_by	- update user
long_url	- required, a long URL to be shortened (example: https://www.idnes.cz). Must contain http/https
client_id	- The client ID of an OAuth app
custom_bitlinks	- update custom_bitlinks
link	- link
id	- id
deeplinks	- string Default: "both" Enum:"on" "off" "both" Filter to only Bitlinks that contain deeplinks

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_update_bitlink(bitlink = "bit.ly/DPetrov", title = "novy titulek")
```

```
## hash is the one which is only returned. Dont use
bitly_update_bitlink(bitlink = "on.natgeo.com/1bEVhwE")

## manyHashes <- list("bit.ly/DPetrov", "bit.ly/1QU8CFm", "bit.ly/1R1LPSE", "bit.ly/1LNqqva")
## for (u in 1:length(manyHashes)) {
##   print(bitly_update_bitlink(bitlink = manyHashes[[u]],
##                             title = stri_rand_strings(1, 8, pattern = "[A-Za-z0-9]"))
## }

## End(Not run)
```

bitly_update_campaign *Update A Channel (Premium)*

Description

Update an existing Channel

Usage

```
bitly_update_campaign(
  campaign_guid = NULL,
  group_guid = NULL,
  channel_guids = NULL,
  description = NULL,
  name = NULL,
  showRequestURL = T
)
```

Arguments

campaign_guid - string | A GUID for a Bitly campaign
group_guid - a GUID for a Bitly group
channel_guids - a list of strings
description - description of campaign
name - its name
showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Campaigns

Bit.ly Campaigns allows you to build and manage omnichannel campaigns.

See Also

<https://dev.bitly.com/api-reference/#updateCampaign>

Examples

```
## Not run:
cc <- bitly_update_campaign(
  group_guid = "", channel_guids = list("1", "2", "3"),
  description = "description", name = "name"
)

## End(Not run)
```

bitly_update_channel *Update A Channel (Premium)*

Description

Update an existing Channel

Usage

```
bitly_update_channel(
  channel_guid = NULL,
  group_guid = NULL,
  guid = NULL,
  name = NULL,
  modified = NULL,
  created = NULL,
  campaign_guid = NULL,
  bitlink_id = NULL,
  showRequestURL = T
)
```

Arguments

channel_guid - GUID of a target channel

group_guid - a GUID for a Bitly group

guid - ID for a channel

name - its name

modified - string | ISO_TIMESTAMP

created - string | ISO_TIMESTAMP

campaign_guid - string | A GUID for a Bitly campaign

bitlink_id - string

showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Campaigns

Bit.ly Campaigns allows you to build and manage omnichannel campaigns.

See Also

<https://dev.bitly.com/api-reference/#updateChannel>

Examples

```
## Not run:
uc <- bitly_update_channel(channel_guid = "testing", group_guid = "", name = "name")

## End(Not run)
```

bitly_update_cust_bitlink

Update Custom Bitlink (Premium)

Description

Move a Keyword to a different Bitlink

Usage

```
bitly_update_cust_bitlink(
  custom_bitlink = NULL,
  bitlink_id = NULL,
  showRequestURL = FALSE
)
```

Arguments

custom_bitlink - A Custom Bitlink made of the domain and keyword

bitlink_id - string

showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

See Also

<https://dev.bitly.com/api-reference/#updateCustomBitlink>

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_update_cust_bitlink(custom_bitlink = "es.pn/SuperBowl", bitlink_id = "")

## End(Not run)
```

bitly_update_group *Update a Group*

Description

Update the details of a group

Usage

```
bitly_update_group(  
  group_id = NA,  
  name = NA,  
  organization_id = NA,  
  showRequestURL = F  
)
```

Arguments

`group_id` - a required string | A GUID for a Bitly group
`name` - username to change
`organization_id`
 - an optional string parameter | A GUID for a Bitly organization
`showRequestURL` - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#updateGroup>
[bitly_update_user()]

Examples

```
## Not run:
ui <- bitly_user_info(showRequestURL = TRUE)
up_group <- bitly_update_group(
  group_id = ui$default_group_guid[1], name = "New Group Name",
  organization_id = "asd"
)

## End(Not run)
```

bitly_update_group_pref

Update Group Preferences

Description

Update preferences for a specific group

Usage

```
bitly_update_group_pref(group_id = NA, domain_pref = NA, showRequestURL = F)
```

Arguments

group_id - a required string | A GUID for a Bitly group
domain_pref - string
showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Group

Groups are a subdivision within an organization. A user will belong to a group within an organization. Most actions on our API will be on behalf of a group. For example, when you shorten a link, it will be on behalf of a user and a group.

See Also

<https://dev.bitly.com/api-reference#updateGroupPreferences>

Examples

```
## Not run:
ui <- bitly_user_info(showRequestURL = TRUE)
group_pref <- bitly_update_group_pref(group_id = ui$default_group_guid[1])

## End(Not run)
```

bitly_update_user *Update your name and/or default group ID*

Description

This will overwrite your (display) username and/or group ID you belong to.

Usage

```
bitly_update_user(default_group_guid = NULL, name = "", showRequestURL = FALSE)
```

Arguments

default_group_guid
- group id to change, see NOTE

name
- username to change

showRequestURL - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

User

User operations such as changing your name or fetching basic user information apply only to the authenticated user.

Note

Applies only to the authenticated user: Changing group/org ID is only permitted to premium users. Thus, if you are a "free" user and will try to change your default group id to something else, you will get an error. In that case, only changing display name is permitted.

See Also

<https://dev.bitly.com/api-reference/#updateUser>

Examples

```
## Not run:
bitly_bearerToken("access token")
# this applies only for "free" users
uu <- bitly_update_user(name = "Malc")

# if you are premium user, you can additionally adjust your group id
uug <- bitly_update_user(name = "Malc", default_group_guid = "TestGroupID")

## End(Not run)
```

bitly_user_info	<i>Retrieve information for the current authenticated user</i>
-----------------	--

Description

Retrieve information for the current authenticated user

Usage

```
bitly_user_info(showRequestURL = FALSE)
```

Arguments

`showRequestURL` - an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Value

`login` - the specified bitly login or the login of the authenticated user

`name` - the user's full/display name

`default_group_guid` - a group to which user belongs

`created` - Timestamp for the moment the user signed up (uses [ymd_hms](#))

`is_active` - whether a user profile is active

`modified` - Timestamp of the last modification to the user profile (uses [ymd_hms](#))

`is_sso_user` - is Single-Sign-On enabled for the user (PREMIUM FEATURE)

`is_2fa_enabled` - is 2 Step verification enabled ?

`email` - user's emails

User

User operations such as changing your name or fetching basic user information apply only to the authenticated user.

See Also

<https://dev.bitly.com/api-reference/#getUser>

Examples

```
## Not run:  
bitly_bearerToken("access token")  
ui <- bitly_user_info(showRequestURL = TRUE)  
  
## End(Not run)
```

bitly_user_metrics_referring_domains

Get Metrics for a Bitlink by referring domains

Description

This endpoint will rollup the click counts to a referrer about a single Bitlink.

Usage

```
bitly_user_metrics_referring_domains(  
  bitlink = NULL,  
  unit = "day",  
  units = -1,  
  size = 50,  
  unit_reference = NULL,  
  showRequestURL = FALSE  
)
```

Arguments

bitlink	- required, a Bitlink made of the domain and hash
unit	- string Default: "day", Enum: "minute" "hour" "day" "week" "month" A unit of time
units	- integer Default: -1 An integer representing the time units to query data for. pass -1 to return all units of time.
size	- string Default: 50 The quantity of items to be returned
unit_reference	- string An ISO-8601 timestamp, indicating the most recent time for which to pull metrics. Will default to current time.
showRequestURL	- an optional T/F value to whether show URL which has been build and requested from server. For debug purposes, default FALSE.

Value

facet - string | One of "countries" "referrers" "referrers_by_domain" "referring_domains" "referring_networks" "shorten_counts"

See Also

See <https://dev.bitly.com/api-reference/#getMetricsForBitlinkByReferringDomains>

Examples

```
## Not run:
bitly_bearerToken("access token")
bitly_user_metrics_referring_domains(
  bitlink = "cnn.it/2HomWGB", unit = "month", units = -1,
  size = 100
)

## End(Not run)
```

isgd_LinksExpand

Expand a short URL to a longer one

Description

See <https://is.gd/apilookupreference.php>

Usage

```
isgd_LinksExpand(shorturl = "", showRequestURL = FALSE)
```

Arguments

shorturl - (optional) You can specify the shorturl parameter if you'd like to pick a shortened URL instead of having is.gd randomly generate one. These must be between 5 and 30 characters long and can only contain alphanumeric characters and underscores. Shortened URLs are case sensitive. Bear in mind that a desired short URL might already be taken (this is very often the case with common words) so if you're using this option be prepared to respond to an error and get an alternative choice from your app's user.

showRequestURL - show URL which has been build and requested from server. For debug purposes.

Examples

```
## Not run:
isgd_LinksExpand(shorturl = "https://is.gd/4oIAXJ", showRequestURL = TRUE)

## End(Not run)
```

isgd_LinksShorten *Given a long URL, returns a short is.gd link.*

Description

See <https://is.gd/apishorteningreference.php>

Usage

```
isgd_LinksShorten(  
  longUrl = "",  
  logstats = "0",  
  shorturl = NULL,  
  showRequestURL = FALSE  
)
```

Arguments

longUrl	- The url parameter is the address that you want to shorten.
logstats	- (optional) Adding the parameter logstats=1 turns on logging of detailed statistics when the shortened URL you create is accessed. This allows you to see how many times the link was accessed on a given day, what pages referred people to the link, what browser visitors were using etc. You can access these stats via the link preview page for your shortened URL (add a hyphen/dash to the end of the shortened URL to get to it). Creating links with statistics turned on has twice the "cost" towards our rate limit of other shortened links, so leave this parameter out of your API call if you don't require statistics on usage. See our usage limits page for more information on this https://is.gd/usagelimits.php .
shorturl	- (optional) You can specify the shorturl parameter if you'd like to pick a shortened URL instead of having is.gd randomly generate one. These must be between 5 and 30 characters long and can only contain alphanumeric characters and underscores. Shortened URLs are case sensitive. Bear in mind that a desired short URL might already be taken (this is very often the case with common words) so if you're using this option be prepared to respond to an error and get an alternative choice from your app's user.
showRequestURL	- show URL which has been build and requested from server. For debug purposes.

Examples

```
## Not run:  
short_lin <- isgd_LinksShorten(longUrl = "https://novinky.cz/", showRequestURL = TRUE)  
  
## End(Not run)
```

is_bitly_user_premium_holder

Check if authenticated user holds premium account

Description

Check if authenticated user holds premium account

Usage

is_bitly_user_premium_holder()

See Also

[bitly_user_info()]

shortenerAddin

Shorten an URL

Description

Call this function as an addin to prompt a url shortener. bit.ly accepts a custom domain, see [bitly_shorten_link](#).

Usage

shortenerAddin()

vgd_LinksExpand

Expand a short URL to a longer one

Description

See <https://v.gd/apilookupreference.php>

Usage

vgd_LinksExpand(shorturl = "", showRequestURL = FALSE)

Arguments

- `shorturl` - (optional) You can specify the `shorturl` parameter if you'd like to pick a shortened URL instead of having v.gd randomly generate one. These must be between 5 and 30 characters long and can only contain alphanumeric characters and underscores. Shortened URLs are case sensitive. Bear in mind that a desired short URL might already be taken (this is very often the case with common words) so if you're using this option be prepared to respond to an error and get an alternative choice from your app's user.
- `showRequestURL` - show URL which has been build and requested from server. For debug purposes.

Examples

```
## Not run:
isgd_LinksExpand(shorturl = "https://v.gd/4oIAXJ", showRequestURL = TRUE)

## End(Not run)
```

`vgd_LinksShorten`

Given a long URL, returns a short v.gd link.

Description

See <https://v.gd/apishorteningreference.php>

Usage

```
vgd_LinksShorten(
  longUrl = "",
  logstats = "0",
  shorturl = NULL,
  showRequestURL = FALSE
)
```

Arguments

- `longUrl` - The url parameter is the address that you want to shorten.
- `logstats` - (optional) Adding the parameter `logstats=1` turns on logging of detailed statistics when the shortened URL you create is accessed. This allows you to see how many times the link was accessed on a given day, what pages referred people to the link, what browser visitors were using etc. You can access these stats via the link preview page for your shortened URL (add a hyphen/dash to the end of the shortened URL to get to it). Creating links with statistics turned on has twice the "cost" towards our rate limit of other shortened links, so leave this parameter out of your API call if you don't require statistics on usage. See our usage limits page for more information on this <https://v.gd/usagelimits.php>.

- `shorturl` - (optional) You can specify the `shorturl` parameter if you'd like to pick a shortened URL instead of having `vzd` randomly generate one. These must be between 5 and 30 characters long and can only contain alphanumeric characters and underscores. Shortened URLs are case sensitive. Bear in mind that a desired short URL might already be taken (this is very often the case with common words) so if you're using this option be prepared to respond to an error and get an alternative choice from your app's user.
- `showRequestURL` - show URL which has been build and requested from server. For debug purposes.

Examples

```
## Not run:  
assd <- vzd_LinksShorten(longUrl = "https://novinky.cz/", showRequestURL = TRUE)  
  
## End(Not run)
```

Index

as_datetime, [13](#), [30](#)

bitly_add_cust_bitlink, [3](#)

bitly_app_details, [4](#)

bitly_bsds, [4](#)

bitly_bsds_overrides, [5](#)

bitly_create_bitlink, [6](#)

bitly_create_campaigns, [7](#)

bitly_create_channel, [8](#)

bitly_expand_link, [9](#)

bitly_qr_create_code, [10](#)

bitly_rate_limits, [11](#)

bitly_retrieve_bitlink, [11](#)

bitly_retrieve_bitlinks_by_groups, [12](#)

bitly_retrieve_campaign, [13](#)

bitly_retrieve_campaigns, [14](#)

bitly_retrieve_channel, [15](#)

bitly_retrieve_channels, [16](#)

bitly_retrieve_clicks, [17](#)

bitly_retrieve_clicks_summary, [18](#)

bitly_retrieve_cust_bitlink, [19](#)

bitly_retrieve_cust_bitlink_clicks_history, [19](#)

bitly_retrieve_cust_bitlink_metrics_destination, [20](#)

bitly_retrieve_destination_metrics, [21](#)

bitly_retrieve_group, [22](#)

bitly_retrieve_group_click_metrics_by_cities, [23](#)

bitly_retrieve_group_click_metrics_by_countries, [24](#)

bitly_retrieve_group_click_metrics_by_devices, [25](#)

bitly_retrieve_group_click_metrics_by_ref_networks, [26](#)

bitly_retrieve_group_feature_usage, [27](#)

bitly_retrieve_group_pref, [27](#)

bitly_retrieve_group_shorten_counts, [28](#)

bitly_retrieve_groups, [22](#)

bitly_retrieve_links_grouped, [29](#)

bitly_retrieve_metrics_by_countries, [31](#)

bitly_retrieve_metrics_by_referrers, [32](#)

bitly_retrieve_metrics_by_referrers_by_domain, [33](#)

bitly_retrieve_org, [34](#)

bitly_retrieve_org_plan_limits, [35](#)

bitly_retrieve_org_shorten_counts, [36](#)

bitly_retrieve_org_shorten_counts_by_group, [37](#)

bitly_retrieve_orgs, [34](#)

bitly_retrieve_sorted_bitlinks_by_groups, [37](#)

bitly_retrieve_sorted_links, [38](#)

bitly_retrieve_tags, [40](#)

bitly_shorten_link, [40](#), [53](#)

bitly_update_bitlink, [41](#)

bitly_update_campaign, [43](#)

bitly_update_channel, [44](#)

bitly_update_cust_bitlink, [45](#)

bitly_update_group, [46](#)

bitly_update_group_pref, [47](#)

bitly_update_user, [48](#)

bitly_user_info, [49](#)

bitly_user_metrics_referring_domains, [50](#)

is_bitly_user_premium_holder, [53](#)

isgd_LinksExpand, [51](#)

isgd_LinksShorten, [52](#)

shortenerAddin, [53](#)

vgd_LinksExpand, [53](#)

vgd_LinksShorten, [54](#)

ymd_hms, [49](#)