

[Apdu](#)[CadClientInterface](#)[CadDevice](#)[CadTransportException](#)[T1Exception](#)[TLP224Exception](#)

## Package com.sun.javacard.apduio

Provides a client API for exchanging APDUs with smart cards.

See:

[Description](#)

### Interface Summary

<a href="#">CadClientInterface</a>	An interface describing a client connection to a card.
------------------------------------	--

### Class Summary

<a href="#">Apdu</a>	This class represent a pair of C-APDU and R-APDU.
<a href="#">CadDevice</a>	Factory class producing CardClientInterface instances (connections to a card)

### Exception Summary

<a href="#">CadTransportException</a>	This abstract class is the parent class of all CAD exception classes.
<a href="#">T1Exception</a>	This class represents error states for T=1 CAD devices.
<a href="#">TLP224Exception</a>	Exceptions related to TLP224 protocol violations

## Package com.sun.javacard.apduio Description

Provides a client API for exchanging APDUs with smart cards.

It is used internally by several components of the Java Card development kit.

**com.sun.javacard.apduio**

## Class Apdu

java.lang.Object

└ com.sun.javacard.apduio.Apdu

```
public class Apdu
```

```
extends java.lang.Object
```

This class represent a pair of C-APDU and R-APDU. It is used internally by several components of the Java Card development kit.

## Field Summary

static int	<a href="#">APDU_TYPE_MASK</a> Mask to extract APDU type information: either ISO ecoding or not.
static int	<a href="#">CASE_1</a> The value which indicates this Apdu is an ISO 7816-3 Case 1 apdu
static int	<a href="#">CASE_2E</a> The value which indicates this Apdu is an ISO 7816-3 Case 2 Extended apdu
static int	<a href="#">CASE_2S</a> The value which indicates this Apdu is an ISO 7816-3 Case 2 Short apdu
static int	<a href="#">CASE_3E</a> The value which indicates this Apdu is an ISO 7816-3 Case 3 Extended apdu
static int	<a href="#">CASE_3S</a> The value which indicates this Apdu is an ISO 7816-3 Case 3 Short apdu

static int	<a href="#"><u>CASE_4E</u></a> The value which indicates this Apdu is an ISO 7816-3 Case 4 Extended apdu
static int	<a href="#"><u>CASE_4S</u></a> The value which indicates this Apdu is an ISO 7816-3 Case 4 Short apdu
static int	<a href="#"><u>CLA</u></a> The offset in the command array to the ISO 7816-3 CLA octet.
byte[]	<a href="#"><u>command</u></a> Internal representation of the C-APDU header
byte[]	<a href="#"><u>dataIn</u></a> Data part of the C-APDU
byte[]	<a href="#"><u>dataOut</u></a> Data part of the R-APDU
static int	<a href="#"><u>INS</u></a> The offset in the command array to the ISO 7816-3 INS octet.
boolean	<a href="#"><u>isExtended</u></a> Extended APDU flag
int	<a href="#"><u>Lc</u></a> Value of Lc
int	<a href="#"><u>Le</u></a> Value of Le
static int	<a href="#"><u>LOGICAL CHN MASK</u></a> Mask to extract channel information out of the CLA byte.
static int	<a href="#"><u>P1</u></a> The offset in the command array to the ISO 7816-3 P1 octet.
static int	<a href="#"><u>P2</u></a> The offset in the command array to the ISO 7816-3 P2 octet.
static int	<a href="#"><u>P3</u></a> The offset in the command array to the ISO 7816-3 P3 octet.
byte[]	<a href="#"><u>sw1sw2</u></a> Status as byte array

## Constructor Summary

## [Apdu](#)( )

Creates a new instance of Apdu.

## Method Summary

int	<a href="#"><u>getCase</u></a> ( )	Return the ISO 7816-3 Case of this Apdu
byte	<a href="#"><u>getChannelInfo</u></a> ( )	Determines the channel number
byte [ ]	<a href="#"><u>getCommand</u></a> ( )	Get internal representation of the header of the C-APDU
byte [ ]	<a href="#"><u>getCommandApduBytes</u></a> ( )	returns the command APDU as a byte array.
byte [ ]	<a href="#"><u>getDataIn</u></a> ( )	Get the data part of the C-APDU
byte [ ]	<a href="#"><u>getDataOut</u></a> ( )	Get the data part of the R-APDU
int	<a href="#"><u>getLc</u></a> ( )	Get Lc
int	<a href="#"><u>getLe</u></a> ( )	Get Le
byte [ ]	<a href="#"><u>getResponseApduBytes</u></a> ( )	returns the response APDU as a byte array.
int	<a href="#"><u>getStatus</u></a> ( )	Get status (SW bytes) as integer
byte [ ]	<a href="#"><u>getSw1Sw2</u></a> ( )	Get status bytes
void	<a href="#"><u>setDataIn</u></a> (byte[ ] dataIn)	Set the data of the C-APDU
void	<a href="#"><u>setDataIn</u></a> (byte[ ] dataIn, int length)	Set the data of the C-APDU
void	<a href="#"><u>setDataOut</u></a> (byte[ ] dataOut)	Set the data part of the R-APDU

void	<a href="#"><b>setDataOut</b></a> (byte[] dataOut, int length) Set the data part of the R-APDU
void	<a href="#"><b>setLc</b></a> (int Lc) Set the value of Lc
void	<a href="#"><b>setLe</b></a> (int Le) Set Le
java.lang.String	<a href="#"><b>toString</b></a> () Generate a string representation of this Apdu in the ApduTool output format.

## Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

## Field Detail

### CLA

public static final int **CLA**

The offset in the command array to the ISO 7816-3 CLA octet.

#### See Also:

[Constant Field Values](#)

### INS

public static final int **INS**

The offset in the command array to the ISO 7816-3 INS octet.

#### See Also:

[Constant Field Values](#)

---

## P1

```
public static final int P1
```

The offset in the command array to the ISO 7816-3 P1 octet.

**See Also:**

[Constant Field Values](#)

---

## P2

```
public static final int P2
```

The offset in the command array to the ISO 7816-3 P2 octet.

**See Also:**

[Constant Field Values](#)

---

## P3

```
public static final int P3
```

The offset in the command array to the ISO 7816-3 P3 octet.

**See Also:**

[Constant Field Values](#)

---

## CASE\_1

```
public static final int CASE_1
```

The value which indicates this Apdu is an ISO 7816-3 Case 1 apdu

**See Also:**

[Constant Field Values](#)

---

## CASE\_2S

```
public static final int CASE_2S
```

The value which indicates this Apdu is an ISO 7816-3 Case 2 Short apdu

**See Also:**

[Constant Field Values](#)

---

## CASE\_3S

```
public static final int CASE_3S
```

The value which indicates this Apdu is an ISO 7816-3 Case 3 Short apdu

**See Also:**

[Constant Field Values](#)

---

## CASE\_4S

```
public static final int CASE_4S
```

The value which indicates this Apdu is an ISO 7816-3 Case 4 Short apdu

**See Also:**

[Constant Field Values](#)

---

## CASE\_2E

```
public static final int CASE_2E
```

The value which indicates this Apdu is an ISO 7816-3 Case 2 Extended apdu

**See Also:**

[Constant Field Values](#)

---

## CASE\_3E

```
public static final int CASE_3E
```

The value which indicates this Apdu is an ISO 7816-3 Case 3 Extended apdu

**See Also:**

[Constant Field Values](#)

---

## CASE\_4E

```
public static final int CASE_4E
```

The value which indicates this Apdu is an ISO 7816-3 Case 4 Extended apdu

**See Also:**

[Constant Field Values](#)

---

## LOGICAL\_CHN\_MASK

```
public static final int LOGICAL_CHN_MASK
```

Mask to extract channel information out of the CLA byte.

**See Also:**

[Constant Field Values](#)

---

## **APDU\_TYPE\_MASK**

```
public static final int APDU_TYPE_MASK
```

Mask to extract APDU type information: either ISO encoding or not.

**See Also:**

[Constant Field Values](#)

---

## **command**

```
public byte[ ] command
```

Internal representation of the C-APDU header

---

## **Lc**

```
public int Lc
```

Value of Lc

---

## **dataIn**

```
public byte[ ] dataIn
```

Data part of the C-APDU

---

## **Le**

```
public int Le
```

Value of Le

---

## **dataOut**

```
public byte[ ] dataOut
```

Data part of the R-APDU

---

## **sw1sw2**

```
public byte[ ] sw1sw2
```

Status as byte array

---

## **isExtended**

```
public boolean isExtended
```

Extended APDU flag

## **Constructor Detail**

### **Apdu**

```
public Apdu( )
```

Creates a new instance of Apdu.

## **Method Detail**

### **getCommand**

```
public byte[ ] getCommand( )
```

Get internal representation of the header of the C-APDU

**Returns:**

The header of the C-APDU

---

## **getDataIn**

```
public byte[ ] getDataIn( )
```

Get the data part of the C-APDU

**Returns:**

The data

---

## **setDataIn**

```
public void setDataIn(byte[ ] dataIn)
```

Set the data of the C-APDU

**Parameters:**

dataIn - The data

---

## **setLc**

```
public void setLc(int Lc)
```

Set the value of Lc

**Parameters:**

Lc - value of the Lc

---

## **setDataIn**

```
public void setDataIn(byte[] dataIn,  
                      int length)
```

Set the data of the C-APDU

### **Parameters:**

  dataIn - The data  
  length - the data length

---

## **getLc**

```
public int getLc()
```

Get Lc

### **Returns:**

  The Lc

---

## **setDataOut**

```
public void setDataOut(byte[] dataOut)
```

Set the data part of the R-APDU

### **Parameters:**

  dataOut - The data

---

## **setLe**

```
public void setLe(int Le)
```

Set Le

**Parameters:**

Le - value of Le

---

## **setDataOut**

```
public void setDataOut(byte[] dataOut,  
                      int length)
```

Set the data part of the R-APDU

**Parameters:**

dataOut - The data  
length - The data length

---

## **getLe**

```
public int getLe()
```

Get Le

**Returns:**

The Le

---

## **getDataOut**

```
public byte[] getDataOut()
```

Get the data part of the R-APDU

**Returns:**

The data part of the R-APDU

---

## **getSw1Sw2**

```
public byte[ ] getSw1Sw2( )
```

Get status bytes

### **Returns:**

The status bytes

---

## **getStatus**

```
public int getStatus( )
```

Get status (SW bytes) as integer

### **Returns:**

The status

---

## **getCase**

```
public int getCase( )
```

Return the ISO 7816-3 Case of this Apdu

### **Returns:**

An int value indicating the ISO case.

---

## **getChannelInfo**

```
public byte getChannelInfo( )
```

Determines the channel number

**Returns:**

The channel number

---

## getCommandApduBytes

```
public byte[ ] getCommandApduBytes( )
```

returns the command APDU as a byte array.

**Returns:**

The command APDU

---

## getResponseApduBytes

```
public byte[ ] getResponseApduBytes( )
```

returns the response APDU as a byte array.

**Returns:**

The response APDU

---

## toString

```
public java.lang.String toString( )
```

Generate a string representation of this Apdu in the ApduTool output format.

**Overrides:**

toString in class java.lang.Object

**Returns:**

String representation of this Apdu

---

[PREV CLASS](#) [NEXT CLASS](#)

SUMMARY: NESTED | [FIELD](#) | [CONSTR](#) | [METHOD](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

DETAIL: [FIELD](#) | [CONSTR](#) | [METHOD](#)

---

com.sun.javacard.apduio

## Interface CadClientInterface

public interface **CadClientInterface**

An interface describing a client connection to a card.

### Method Summary

void	<a href="#">exchangeApdu</a> ( <a href="#">Apdu</a> apdu)	Exchanges com.sun.javacard.apduio.Apdu with a card.
void	<a href="#">powerDown</a> ( )	Powerdown a card or simulator and then disconnect
void	<a href="#">powerDown</a> (boolean disconnect)	Send powerdown to a card
byte [ ]	<a href="#">powerUp</a> ( )	Send powerup to a card or a simulator

### Method Detail

#### **exchangeApdu**

```
void exchangeApdu(Apdu apdu)
                  throws java.io.IOException,
                     CadTransportException
```

Exchanges com.sun.javacard.apduio.Apdu with a card.

**Parameters:**

apdu - A pair of C-APDU and R-APDU

**Throws:**

[java.io.IOException](#) - Communication error

[CadTransportException](#) - Protocol error

---

## powerDown

```
void powerDown(boolean disconnect)
               throws java.io.IOException,
                  CadTransportException
```

Send powerdown to a card

**Parameters:**

disconnect - This parameter is applicable to card simulators only. true = disconnect from the simulator false = powedown, but leave the connection open

**Throws:**

[java.io.IOException](#) - Communication error

[CadTransportException](#) - Protocol error

---

## powerDown

```
void powerDown()
               throws java.io.IOException,
                  CadTransportException
```

Powerdown a card or simulator and then disconnect

**Throws:**

[java.io.IOException](#) - Communication error

[CadTransportException](#) - Protocol error

---

## powerUp

```
byte[ ] powerUp( )
    throws java.io.IOException,
        CadTransportException
```

Send powerup to a card or a simulator

**Returns:**

ATR bytes

**Throws:**

java.io.IOException - Communication error

[CadTransportException](#) - Protocol error

---

[Package](#) [Class](#) [Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV CLASS](#) [NEXT CLASS](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

SUMMARY: NESTED | FIELD | CONSTR | [METHOD](#)

DETAIL: FIELD | CONSTR | [METHOD](#)

---

**com.sun.javacard.apduio**

## Class CadDevice

java.lang.Object

└ com.sun.javacard.apduio.CadDevice

public abstract class **CadDevice**

extends java.lang.Object

Factory class producing CardClientInterface instances (connections to a card)

## Field Summary

protected static java.util.ResourceBundle	<a href="#"><b>messages</b></a> Properties file with messages
protected boolean	<a href="#"><b>debug</b></a> Internal debug flag.
protected byte	<a href="#"><b>deviceProtocol</b></a> The current used protocol
protected java.io.InputStream	<a href="#"><b>in</b></a> The input stream which data is read from.
protected java.io.OutputStream	<a href="#"><b>out</b></a> The output stream to which data is written.
static byte	<a href="#"><b>PROTOCOL_PCSC</b></a> PC/SC constant
static byte	<a href="#"><b>PROTOCOL_T0</b></a> Protocol constant
static byte	<a href="#"><b>PROTOCOL_T1</b></a> Protocol constant

static byte	<a href="#"><u>PROTOCOL_TCL</u></a>
	Protocol constant

## Constructor Summary

protected	<a href="#"><u>CadDevice</u></a> (byte devProtocolType) this form of constructor is used by PCSC streams are not applicable
protected	<a href="#"><u>CadDevice</u></a> (byte devProtocolType, java.io.InputStream in, java.io.OutputStream out) this form of constructor is used by T=0, T=1 implementations

## Method Summary

void	<a href="#"><u>close</u></a> ( ) Flush and close the input and output streams.
static <a href="#"><u>CadClientInterface</u></a>	<a href="#"><u>getCadClientInstance</u></a> (byte protocolType, java.io.InputStream in, java.io.OutputStream out) A factory method
byte	<a href="#"><u>getDeviceProtocol</u></a> ( ) Get the value of the protocol byte
static <a href="#"><u>CadClientInterface</u></a>	<a href="#"><u>getPCSCClientInstance</u></a> (int readerNumber) A factory method for connecting to a PCSC card reader

## Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Field Detail

### messages

protected static java.util.ResourceBundle messages

Properties file with messages

---

### in

protected java.io.InputStream in

---

The input stream which data is read from. This field is used to store the reference to the input stream which an instance of the Cad class reads from.

---

## **out**

```
protected java.io.OutputStream out
```

The output stream to which data is written. This field is used to store the reference to the output stream which an instance of the Cad class writes to.

---

## **debug**

```
protected boolean debug
```

Internal debug flag. Set the system property apduIODebug to 0x01 to activate transport level debugging.

---

## **PROTOCOL\_T0**

```
public static final byte PROTOCOL_T0
```

Protocol constant

**See Also:**

[Constant Field Values](#)

---

## **PROTOCOL\_T1**

```
public static final byte PROTOCOL_T1
```

Protocol constant

**See Also:**

[Constant Field Values](#)

---

## **PROTOCOL\_TCL**

```
public static final byte PROTOCOL_TCL
```

Protocol constant

**See Also:**

[Constant Field Values](#)

---

## PROTOCOL\_PCSC

```
public static final byte PROTOCOL_PCSC
```

PC/SC constant

**See Also:**

[Constant Field Values](#)

---

## deviceProtocol

```
protected byte deviceProtocol
```

The current used protocol

### Constructor Detail

## CadDevice

```
protected CadDevice(byte devProtocolType,  
                   java.io.InputStream in,  
                   java.io.OutputStream out)
```

this form of constructor is used by T=0, T=1 implementations

**Parameters:**

devProtocolType - Procol constant: T1 or T1  
in - Input stream from a simulator or a TLP224 card reader  
out - Output stream to a simulator or a TLP224 card reader

---

## CadDevice

```
protected CadDevice(byte devProtocolType)
```

this form of constructor is used by PCSC streams are not applicable

### Parameters:

devProtocolType - Protocol type (PCSC)

## Method Detail

### getDeviceProtocol

```
public byte getDeviceProtocol()
```

Get the value of the protocol byte

### Returns:

the value of the protocol byte

---

### getCadClientInstance

```
public static CadClientInterface getCadClientInstance(byte protocolType,  
                                                    java.io.InputStream in,  
                                                    java.io.OutputStream out)
```

A factory method

### Parameters:

protocolType - Protocol constant  
in - Input stream from a simulator  
out - Output stream to a simulator

### Returns:

New instance of a card connection

---

### getPCSCClientInstance

```
public static CadClientInterface getPCSCClientInstance(int readerNumber)
```

A factory method for connecting to a PCSC card reader

**Parameters:**

readerNumber - PC/SC reader number (0, 1, 2...)

**Returns:**

Connection to the reader

---

**close**

```
public void close()
    throws java.io.IOException
```

Flush and close the input and output streams.

**Throws:**

java.io.IOException - If there is an error closing or flushing the input or output streams.

[Package](#) [Class](#) [Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV CLASS](#) [NEXT CLASS](#)

SUMMARY: NESTED | [FIELD](#) | [CONSTR](#) | [METHOD](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

DETAIL: [FIELD](#) | [CONSTR](#) | [METHOD](#)

---

com.sun.javacard.apduio

## Class CadTransportException

java.lang.Object

  └ java.lang.Throwable

    └ java.lang.Exception

      └ com.sun.javacard.apduio.CadTransportException

### All Implemented Interfaces:

[T1Exception](#), [TLP224Exception](#)

---

public abstract class **CadTransportException**

extends java.lang.Exception

This abstract class is the parent class of all CAD exception classes. It serves as an ancestor for T1Exception (for T=1 CAD) as well as TLP225Exception (for T=0 CAD) classes.

### See Also:

## Field Summary

protected	
-----------	--

static	java.
--------	-------

util.	
-------	--

	<a href="#">messages</a>
--	--------------------------

	Properties file with messages
--	-------------------------------

ResourceBundle	
----------------	--

protected int	<a href="#"><b>status</b></a> Error code
static int	<a href="#"><b>STATUS_UNKNOWN</b></a> Error code constant

## Constructor Summary

[\*\*CadTransportException\*\*](#)(int status)

Constructor method for exception class.

## Method Summary

java.lang.String	<a href="#"><b>getMessage()</b></a> Returns a String describing this exception.
------------------	--

int	<a href="#"><b>getStatus()</b></a> Returns the status associated with the exception.
-----	---

### Methods inherited from class java.lang.Throwable

fillInStackTrace, getCause, getLocalizedMessage, getStackTrace, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

## Field Detail

### \_messages

protected static java.util.ResourceBundle \_messages

Properties file with messages

## **status**

```
protected int status
```

Error code

---

## **STATUS\_UNKNOWN**

```
public static int STATUS_UNKNOWN
```

Error code constant

## **Constructor Detail**

### **CadTransportException**

```
public CadTransportException(int status)
```

Constructor method for exception class.

#### **Parameters:**

status - Initialization status for this exception.

## **Method Detail**

### **getStatus**

```
public int getStatus()
```

Returns the status associated with the exception.

#### **Returns:**

The error status

---

## getMessage

```
public java.lang.String getMessage()
```

Returns a String describing this exception.

**Overrides:**

    getMessage in class java.lang.Throwable

**Returns:**

    the String describing this exception

---

[Package](#) [Class](#) [Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV CLASS](#) [NEXT CLASS](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

SUMMARY: NESTED | [FIELD](#) | [CONSTR](#) | [METHOD](#)

DETAIL: [FIELD](#) | [CONSTR](#) | [METHOD](#)

---

com.sun.javacard.apduio

## Class T1Exception

java.lang.Object

  └ java.lang.Throwable

    └ java.lang.Exception

      └ [com.sun.javacard.apduio.CadTransportException](#)

      └ [com.sun.javacard.apduio.T1Exception](#)

### All Implemented Interfaces:

---

public class **T1Exception**

extends [CadTransportException](#)

This class represents error states for T=1 CAD devices.

### See Also:

---

## Field Summary

static int	<a href="#">T1_BAD_CHECKSUM</a>
------------	---------------------------------

static int	<a href="#">T1_BLOCK_IO_ERROR</a>
------------	-----------------------------------

static int	<a href="#">T1_FUNCTION_NOT_SUPPORTED</a>
------------	---

static int	<a href="#"><u>T1_PROTOCOL_VIOLATION</u></a>
static int	<a href="#"><u>T1_UNINITIALIZED</u></a>
static int	<a href="#"><u>T1_WRONG_LENGTH</u></a>

## Fields inherited from class com.sun.javacard.apduio.[CadTransportException](#)

[messages](#), [status](#), [STATUS\\_UNKNOWN](#)

## Constructor Summary

[T1Exception](#)(int status)

Constructor method for this exception class.

## Method Summary

java.  
lang.  
String

[toString](#)()

Returns a String describing this exception.

## Methods inherited from class com.sun.javacard.apduio.[CadTransportException](#)

[getMessage](#), [getStatus](#)

## Methods inherited from class java.lang.Throwable

[fillInStackTrace](#), [getCause](#), [getLocalizedMessage](#), [getStackTrace](#), [initCause](#), [printStackTrace](#), [printStackTrace](#), [printStackTrace](#), [setStackTrace](#)

## Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [wait](#), [wait](#), [wait](#)

## Field Detail

### T1\_WRONG\_LENGTH

```
public static final int T1_WRONG_LENGTH
```

See Also:

[Constant Field Values](#)

---

### T1\_UNINITIALIZED

```
public static final int T1_UNINITIALIZED
```

See Also:

[Constant Field Values](#)

---

### T1\_BLOCK\_IO\_ERROR

```
public static final int T1_BLOCK_IO_ERROR
```

See Also:

[Constant Field Values](#)

---

### T1\_FUNCTION\_NOT\_SUPPORTED

```
public static final int T1_FUNCTION_NOT_SUPPORTED
```

See Also:

[Constant Field Values](#)

---

### T1\_PROTOCOL\_VIOLATION

```
public static final int T1_PROTOCOL_VIOLATION
```

See Also:

[Constant Field Values](#)

---

## T1\_BAD\_CHECKSUM

```
public static final int T1_BAD_CHECKSUM
```

See Also:

[Constant Field Values](#)

## Constructor Detail

### T1Exception

```
public T1Exception(int status)
```

Constructor method for this exception class.

#### Parameters:

status - Initialization status for this exception.

## Method Detail

### toString

```
public java.lang.String toString()
```

Returns a String describing this exception.

#### Overrides:

toString in class java.lang.Throwable

---



com.sun.javacard.apduio

## Class TLP224Exception

java.lang.Object

  └ java.lang.Throwable

    └ java.lang.Exception

      └ [com.sun.javacard.apduio.CadTransportException](#)

      └ **com.sun.javacard.apduio.TLP224Exception**

### All Implemented Interfaces:

public class **TLP224Exception**

extends [CadTransportException](#)

Exceptions related to TLP224 protocol violations

### See Also:

## Field Summary

Fields inherited from class com.sun.javacard.apduio.[CadTransportException](#)

[messages](#), [status](#), [STATUS\\_UNKNOWN](#)

## Constructor Summary

[\*\*TLP224Exception\*\*](#)(int status)

Constructor

## Method Summary

java.  
lang.  
String      [\*\*toString\(\)\*\*](#)

Returns a String describing this exception.

## Methods inherited from class com.sun.javacard.apduio.[\*\*CadTransportException\*\*](#)

[\*\*getMessage\*\*](#), [\*\*getStatus\*\*](#)

## Methods inherited from class java.lang.Throwable

[\*\*fillInStackTrace\*\*](#), [\*\*getCause\*\*](#), [\*\*getLocalizedMessage\*\*](#), [\*\*getStackTrace\*\*](#),  
[\*\*initCause\*\*](#), [\*\*printStackTrace\*\*](#), [\*\*printStackTrace\*\*](#), [\*\*printStackTrace\*\*](#),  
[\*\*setStackTrace\*\*](#)

## Methods inherited from class java.lang.Object

[\*\*clone\*\*](#), [\*\*equals\*\*](#), [\*\*finalize\*\*](#), [\*\*getClass\*\*](#), [\*\*hashCode\*\*](#), [\*\*notify\*\*](#), [\*\*notifyAll\*\*](#),  
[\*\*wait\*\*](#), [\*\*wait\*\*](#), [\*\*wait\*\*](#)

## Constructor Detail

### **TLP224Exception**

public [\*\*TLP224Exception\*\*](#)(int status)

Constructor

#### **Parameters:**

status - status code

## Method Detail

### **toString**

```
public java.lang.String toString()
```

Returns a String describing this exception.

**Overrides:**

**toString** in class `java.lang.Throwable`

**Returns:**

String describing this exception.

---

[Package](#) [Class](#) [Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV CLASS](#) [NEXT CLASS](#)

SUMMARY: NESTED | [FIELD](#) | [CONSTR](#) | [METHOD](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

DETAIL: FIELD | [CONSTR](#) | [METHOD](#)

---

## Package com.sun.javacard.apduio

Provides a client API for exchanging APDUs with smart cards.

See:

[Description](#)

### Interface Summary

<a href="#">CadClientInterface</a>	An interface describing a client connection to a card.
------------------------------------	--

### Class Summary

<a href="#">Apdu</a>	This class represent a pair of C-APDU and R-APDU.
<a href="#">CadDevice</a>	Factory class producing CardClientInterface instances (connections to a card)

### Exception Summary

<a href="#">CadTransportException</a>	This abstract class is the parent class of all CAD exception classes.
<a href="#">T1Exception</a>	This class represents error states for T=1 CAD devices.
<a href="#">TLP224Exception</a>	Exceptions related to TLP224 protocol violations

## Package com.sun.javacard.apduio Description

Provides a client API for exchanging APDUs with smart cards.

It is used internally by several components of the Java Card development kit.



## Hierarchy For Package com.sun.javacard.apduio

### Class Hierarchy

- o java.lang.Object
  - o com.sun.javacard.apduio.[Apdu](#)
  - o com.sun.javacard.apduio.[CadDevice](#)
  - o java.lang.Throwable
    - o java.lang.Exception
      - o com.sun.javacard.apduio.[CadTransportException](#)
        - o com.sun.javacard.apduio.[T1Exception](#)
        - o com.sun.javacard.apduio.[TLP224Exception](#)

### Interface Hierarchy

- o com.sun.javacard.apduio.[CadClientInterface](#)

---

## Deprecated API

---

### Contents

---

## A

### [Apdu](#) - Class in [com.sun.javacard.apduio](#)

This class represent a pair of C-APDU and R-APDU.

### [Apdu\(\)](#) - Constructor for class com.sun.javacard.apduio.[Apdu](#)

Creates a new instance of Apdu.

### [APDU\\_TYPE\\_MASK](#) - Static variable in class com.sun.javacard.apduio.[Apdu](#)

Mask to extract APDU type information: either ISO ecoding or not.

## C

### [CardClientInterface](#) - Interface in [com.sun.javacard.apduio](#)

An interface describing a client connection to a card.

### [CardDevice](#) - Class in [com.sun.javacard.apduio](#)

Factory class producing CardClientInterface instances (connections to a card)

### [CardDevice\(byte, InputStream, OutputStream\)](#) - Constructor for class com.sun.javacard.apduio.

### [CardDevice](#)

this form of constructor is used by T=0, T=1 implementations

### [CardDevice\(byte\)](#) - Constructor for class com.sun.javacard.apduio.[CardDevice](#)

this form of constructor is used by PCSC streams are not applicable

### [CardTransportException](#) - Exception in [com.sun.javacard.apduio](#)

This abstract class is the parent class of all CAD exception classes.

### [CardTransportException\(int\)](#) - Constructor for exception com.sun.javacard.apduio.

### [CardTransportException](#)

Constructor method for exception class.

### [CASE\\_1](#) - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The value which indicates this Apdu is an ISO 7816-3 Case 1 apdu

### [CASE\\_2E](#) - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The value which indicates this Apdu is an ISO 7816-3 Case 2 Extended apdu

### [CASE\\_2S](#) - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The value which indicates this Apdu is an ISO 7816-3 Case 2 Short apdu

### [CASE\\_3E](#) - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The value which indicates this Apdu is an ISO 7816-3 Case 3 Extended apdu

**CASE\_3S** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The value which indicates this Apdu is an ISO 7816-3 Case 3 Short apdu

**CASE\_4E** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The value which indicates this Apdu is an ISO 7816-3 Case 4 Extended apdu

**CASE\_4S** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The value which indicates this Apdu is an ISO 7816-3 Case 4 Short apdu

**CLA** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The offset in the command array to the ISO 7816-3 CLA octet.

**close()** - Method in class com.sun.javacard.apduio.[CadDevice](#)

Flush and close the input and output streams.

**com.sun.javacard.apduio** - package com.sun.javacard.apduio

Provides a client API for exchanging APDUs with smart cards.

**command** - Variable in class com.sun.javacard.apduio.[Apdu](#)

Internal representation of the C-APDU header

---

## D

**dataIn** - Variable in class com.sun.javacard.apduio.[Apdu](#)

Data part of the C-APDU

**dataOut** - Variable in class com.sun.javacard.apduio.[Apdu](#)

Data part of the R-APDU

**debug** - Variable in class com.sun.javacard.apduio.[CadDevice](#)

Internal debug flag.

**deviceProtocol** - Variable in class com.sun.javacard.apduio.[CadDevice](#)

The current used protocol

---

## E

**exchangeApdu(Apdu)** - Method in interface com.sun.javacard.apduio.[CadClientInterface](#)

Exchanges com.sun.javacard.apduio.Apdu with a card.

---

## G

**getCadClientInstance(byte, InputStream, OutputStream)** - Static method in class com.sun.javacard.apduio.[CadDevice](#)

A factory method

**getCase()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Return the ISO 7816-3 Case of this Apdu

**getChannelInfo()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Determines the channel number

**getCommand()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Get internal representation of the header of the C-APDU

**getCommandApduBytes()** - Method in class com.sun.javacard.apduio.[Apdu](#)

returns the command APDU as a byte array.

**getDataIn()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Get the data part of the C-APDU

**getDataOut()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Get the data part of the R-APDU

**getDeviceProtocol()** - Method in class com.sun.javacard.apduio.[CadDevice](#)

Get the value of the protocol byte

**getLc()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Get Lc

**getLe()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Get Le

**getMessage()** - Method in exception com.sun.javacard.apduio.[CadTransportException](#)

Returns a String describing this exception.

**getPCSCClientInstance(int)** - Static method in class com.sun.javacard.apduio.[CadDevice](#)

A factory method for connecting to a PCSC card readed

**getResponseApduBytes()** - Method in class com.sun.javacard.apduio.[Apdu](#)

returns the response APDU as a byte array.

**getStatus()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Get status (SW bytes) as integer

**getStatus()** - Method in exception com.sun.javacard.apduio.[CadTransportException](#)

Returns the status associated with the exception.

**getSw1Sw2()** - Method in class com.sun.javacard.apduio.[Apdu](#)

Get status bytes

---

**in** - Variable in class com.sun.javacard.apduio.[CadDevice](#)

The input stream which data is read from.

**INS** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The offset in the command array to the ISO 7816-3 INS octet.

**isExtended** - Variable in class com.sun.javacard.apduio.[Apdu](#)

Extended APDU flag

---

## L

**Lc** - Variable in class com.sun.javacard.apduio.[Apdu](#)

Value of Lc

**Le** - Variable in class com.sun.javacard.apduio.[Apdu](#)

Value of Le

**LOGICAL\_CHN\_MASK** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

Mask to extract channel information out of the CLA byte.

---

## O

**out** - Variable in class com.sun.javacard.apduio.[CadDevice](#)

The output stream to which data is written.

---

## P

**P1** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The offset in the command array to the ISO 7816-3 P1 octet.

**P2** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The offset in the command array to the ISO 7816-3 P2 octet.

**P3** - Static variable in class com.sun.javacard.apduio.[Apdu](#)

The offset in the command array to the ISO 7816-3 P3 octet.

**powerDown(boolean)** - Method in interface com.sun.javacard.apduio.[CadClientInterface](#)

Send powerdown to a card

**powerDown()** - Method in interface com.sun.javacard.apduio.[CadClientInterface](#)

Powerdown a card or simulator and then disconnect

**powerUp()** - Method in interface com.sun.javacard.apduio.[CadClientInterface](#)

Send powerup to a card or a simulator

**PROTOCOL\_PCSC** - Static variable in class com.sun.javacard.apduio.[CadDevice](#)

PC/SC constant

**PROTOCOL\_T0** - Static variable in class com.sun.javacard.apduio.[CadDevice](#)

Protocol constant

**PROTOCOL\_T1** - Static variable in class com.sun.javacard.apduio.[CadDevice](#)

Protocol constant

**PROTOCOL\_TCL** - Static variable in class com.sun.javacard.apduio.[CadDevice](#)

Protocol constant

---

## S

**setDataIn(byte[])** - Method in class com.sun.javacard.apduio.[Apdu](#)

Set the data of the C-APDU

**setDataIn(byte[], int)** - Method in class com.sun.javacard.apduio.[Apdu](#)

Set the data of the C-APDU

**setDataOut(byte[])** - Method in class com.sun.javacard.apduio.[Apdu](#)

Set the data part of the R-APDU

**setDataOut(byte[], int)** - Method in class com.sun.javacard.apduio.[Apdu](#)

Set the data part of the R-APDU

**setLc(int)** - Method in class com.sun.javacard.apduio.[Apdu](#)

Set the value of Lc

**setLe(int)** - Method in class com.sun.javacard.apduio.[Apdu](#)

Set Le

**status** - Variable in exception com.sun.javacard.apduio.[CadTransportException](#)

Error code

**STATUS\_UNKNOWN** - Static variable in exception com.sun.javacard.apduio.[CadTransportException](#)

Error code constant

**sw1sw2** - Variable in class com.sun.javacard.apduio.[Apdu](#)

Status as byte array

---

## T

**T1\_BAD\_CHECKSUM** - Static variable in exception com.sun.javacard.apduio.[T1Exception](#)

**T1\_BLOCK\_IO\_ERROR** - Static variable in exception com.sun.javacard.apduio.[T1Exception](#)

[\*\*T1\\_FUNCTION\\_NOT\\_SUPPORTED\*\*](#) - Static variable in exception com.sun.javacard.apduio.[T1Exception](#)

[\*\*T1\\_PROTOCOL\\_VIOLATION\*\*](#) - Static variable in exception com.sun.javacard.apduio.[T1Exception](#)

[\*\*T1\\_UNINITIALIZED\*\*](#) - Static variable in exception com.sun.javacard.apduio.[T1Exception](#)

[\*\*T1\\_WRONG\\_LENGTH\*\*](#) - Static variable in exception com.sun.javacard.apduio.[T1Exception](#)

[\*\*T1Exception\*\*](#) - Exception in [com.sun.javacard.apduio](#)

This class represents error states for T=1 CAD devices.

[\*\*T1Exception\(int\)\*\*](#) - Constructor for exception com.sun.javacard.apduio.[T1Exception](#)

Constructor method for this exception class.

[\*\*TLP224Exception\*\*](#) - Exception in [com.sun.javacard.apduio](#)

Exceptions related to TLP224 protocol violations

[\*\*TLP224Exception\(int\)\*\*](#) - Constructor for exception com.sun.javacard.apduio.[TLP224Exception](#)

Constructor

[\*\*toString\(\)\*\*](#) - Method in class com.sun.javacard.apduio.[Apdu](#)

Generate a string representation of this Apdu in the ApduTool output format.

[\*\*toString\(\)\*\*](#) - Method in exception com.sun.javacard.apduio.[T1Exception](#)

Returns a String describing this exception.

[\*\*toString\(\)\*\*](#) - Method in exception com.sun.javacard.apduio.[TLP224Exception](#)

Returns a String describing this exception.

---

[\*\*messages\*\*](#) - Static variable in class com.sun.javacard.apduio.[CadDevice](#)

Properties file with messages

[\*\*messages\*\*](#) - Static variable in exception com.sun.javacard.apduio.[CadTransportException](#)

Properties file with messages

---

[A](#) [C](#) [D](#) [E](#) [G](#) [I](#) [L](#) [O](#) [P](#) [S](#) [T](#) [\\_](#)

[Package](#) [Class](#) [Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV](#) [NEXT](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

## How This API Document Is Organized

This API (Application Programming Interface) document has pages corresponding to the items in the navigation bar, described as follows.

### Package

Each package has a page that contains a list of its classes and interfaces, with a summary for each. This page can contain four categories:

- Interfaces (*italic*)
- Classes
- Enums
- Exceptions
- Errors
- Annotation Types

### Class/Interface

Each class, interface, nested class and nested interface has its own separate page. Each of these pages has three sections consisting of a class/interface description, summary tables, and detailed member descriptions:

- Class inheritance diagram
- Direct Subclasses
- All Known Subinterfaces
- All Known Implementing Classes
- Class/interface declaration
- Class/interface description
- Nested Class Summary
- Field Summary
- Constructor Summary
- Method Summary
- Field Detail

- Constructor Detail
- Method Detail

Each summary entry contains the first sentence from the detailed description for that item. The summary entries are alphabetical, while the detailed descriptions are in the order they appear in the source code. This preserves the logical groupings established by the programmer.

## Annotation Type

Each annotation type has its own separate page with the following sections:

- Annotation Type declaration
- Annotation Type description
- Required Element Summary
- Optional Element Summary
- Element Detail

## Enum

Each enum has its own separate page with the following sections:

- Enum declaration
- Enum description
- Enum Constant Summary
- Enum Constant Detail

## Tree (Class Hierarchy)

There is a [Class Hierarchy](#) page for all packages, plus a hierarchy for each package. Each hierarchy page contains a list of classes and a list of interfaces. The classes are organized by inheritance structure starting with `java.lang.Object`. The interfaces do not inherit from `java.lang.Object`.

- When viewing the Overview page, clicking on "Tree" displays the hierarchy for all packages.
- When viewing a particular package, class or interface page, clicking "Tree" displays the hierarchy for only that package.

## Deprecated API

The [Deprecated API](#) page lists all of the API that have been deprecated. A deprecated API is not recommended for use, generally due to improvements, and a replacement API is usually given. Deprecated APIs may be removed in future implementations.

## Index

The [Index](#) contains an alphabetic list of all classes, interfaces, constructors, methods, and fields.

## Prev/Next

These links take you to the next or previous class, interface, package, or related page.

## Frames/No Frames

These links show and hide the HTML frames. All pages are available with or without frames.

## Constant Field Values

The [Constant Field Values](#) page lists the static final fields and their values.

*This help file applies to API documentation generated using the standard doclet.*

---

[Package](#) [Class](#) [Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV](#) [NEXT](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

---

## All Classes

[Apdu](#)

[CadClientInterface](#)

[CadDevice](#)

[CadTransportException](#)

[T1Exception](#)

[TLP224Exception](#)

## Constant Field Values

### Contents

- [com.sun.\\*](#)

### com.sun.\*

#### [com.sun.javacard.apduio.Apdu](#)

public static final int	<a href="#">APDU_TYPE_MASK</a>	240
public static final int	<a href="#">CASE_1</a>	1
public static final int	<a href="#">CASE_2E</a>	5
public static final int	<a href="#">CASE_2S</a>	2
public static final int	<a href="#">CASE_3E</a>	6
public static final int	<a href="#">CASE_3S</a>	3
public static final int	<a href="#">CASE_4E</a>	7
public static final int	<a href="#">CASE_4S</a>	4
public static final int	<a href="#">CLA</a>	0
public static final int	<a href="#">INS</a>	1
public static final int	<a href="#">LOGICAL_CHN_MASK</a>	3
public static final int	<a href="#">P1</a>	2
public static final int	<a href="#">P2</a>	3
public static final int	<a href="#">P3</a>	4

#### [com.sun.javacard.apduio.CadDevice](#)

public static final byte	<a href="#">PROTOCOL_PCSC</a>	-85
public static final byte	<a href="#">PROTOCOL_T0</a>	0
public static final byte	<a href="#">PROTOCOL_T1</a>	1
public static final byte	<a href="#">PROTOCOL_TCL</a>	91

## [\*\*com.sun.javacard.apduio.T1Exception\*\*](#)

public static final int	<a href="#">T1_BAD_CHECKSUM</a>	-123
public static final int	<a href="#">T1_BLOCK_IO_ERROR</a>	-126
public static final int	<a href="#">T1_FUNCTION_NOT_SUPPORTED</a>	-125
public static final int	<a href="#">T1_PROTOCOL_VIOLATION</a>	-124
public static final int	<a href="#">T1_UNINITIALIZED</a>	-127
public static final int	<a href="#">T1_WRONG_LENGTH</a>	-128

[Package](#) [Class](#) [Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV](#) [NEXT](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

---

## Hierarchy For All Packages

### Package Hierarchies:

[com.sun.javacard.apduio](#)

---

## Class Hierarchy

- `java.lang.Object`
  - `com.sun.javacard.apduio.Apdu`
  - `com.sun.javacard.apduio.CadDevice`
  - `java.lang.Throwable`
    - `java.lang.Exception`
      - `com.sun.javacard.apduio.CadTransportException`
        - `com.sun.javacard.apduio.T1Exception`
        - `com.sun.javacard.apduio.TLP224Exception`

## Interface Hierarchy

- `com.sun.javacard.apduio.CadClientInterface`
-

Copyright © 2009 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.sun.com/patents> and one or more additional patents or pending patent applications in the U.S. and in other countries.

U.S. Government Rights - Commercial Software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

Sun, Sun Microsystems, the Sun logo, Java, Solaris, Java Card, Mozilla, Netscape, Javadoc, JDK, JVM and NetBeans are trademarks or registered trademarks of Sun Microsystems, Inc. or its subsidiaries, in the U.S. and other countries.

UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Products covered by and information contained in this service manual are controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

---

Copyright © 2009 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, Etats-Unis. Tous droits réservés.

Sun Microsystems, Inc. détient les droits de propriété intellectuelle relatifs à la technologie incorporée dans le produit qui est décrit dans ce document. En particulier, et ce sans limitation, ces droits de propriété intellectuelle peuvent inclure un ou plusieurs des brevets américains listés à l'adresse suivante: <http://www.sun.com/patents> et un ou plusieurs brevets supplémentaires ou les applications de brevet en attente aux États - Unis et dans les autres pays.

Droits du gouvernement des États-Unis - Logiciel Commercial. Les droits des utilisateur du gouvernement des États-Unis sont soumis aux termes de la licence standard Sun Microsystems et aux conditions appliquées de la FAR et de ces compléments.

Sun, Sun Microsystems, le logo Sun, Java, Solaris, Java Card, Mozilla, Netscape, Javadoc, JDK, JVM et NetBeans sont des marques de fabrique ou des marques déposées enregistrées de Sun Microsystems, Inc. ou ses filiales, aux États-Unis et dans d'autres pays.

UNIX est une marque déposée aux États-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Les produits qui font l'objet de ce manuel d'entretien et les informations qu'il contient sont régis par la législation américaine en matière de contrôle des exportations et peuvent être soumis au droit d'autres pays dans le domaine des exportations et importations. Les utilisations finales, ou utilisateurs finaux, pour des armes nucléaires, des missiles, des armes biologiques et chimiques ou du nucléaire maritime, directement ou indirectement, sont strictement interdites. Les exportations ou reexportations vers des pays sous embargo des États-Unis, ou vers des entités figurant sur les listes d'exclusion d'exportation américaines, y compris, mais de manière non exclusive, la liste de personnes qui font l'objet d'un ordre de ne pas participer, d'une façon directe ou indirecte, aux exportations de des produits ou des services qui sont régis par la législation américaine sur le contrôle des exportations et la liste de ressortissants spécifiquement designés, sont rigoureusement interdites.

LA DOCUMENTATION EST FOURNIE "EN L'ÉTAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISÉE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE À LA QUALITÉ MARCHANDE, À L'APTITUDE À UNE UTILISATION PARTICULIÈRE OU À L'ABSENCE DE CONTREFAÇON.